



规格说明: Specifications:
电气特性: Electrical:

1. 额定电流: Current Rating
1.0A/contact terminal
2. 额定电压: Voltage Rating
30V DC
3. 接触阻抗: Contact Resistance
50 milliohms MAX
4. 耐电压: Dielectric Withstanding Voltage:
300 V AC AT Sea Level
5. 绝缘阻抗: Insulation Resistance:
100MEGA ohms MIN

原材料: Raw material:

1. 塑胶: Plastic cement:
Hing Temperature Thermoplastics,
LCP Black/Nature
2. 端子: Contact: Copper Alloy C5191/C2680
3. 外壳: Shell: Copper Alloy C2680
- 电镀: Electroplate:

1. 端子: Contact: Plated Gold in Mating Area;
Tin On Solder Talls
2. 外壳: Shell:
Nickel Plating

③	Shell	—	1	Copper alloy	Ni Plated	—
②	Contact	—	5	Copper alloy	Ag Plated	—
①	Housing	—	1	LCP	None	—
ITEM	PART NAME	TER'NO.	QTY.	MATERIAL	FINISHING	REMARK

APPROVALS		DATE	ELECTRONICS CO.,LTD			
DRAWN	JKUNLU	2018/8/1	HROE			
CHECKED			USB CONNECTOR			
APPROVALS			PART NO.	U-M-M5DD-W-3		

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.	TOLERANCES ARE	30~0.15	±0.30	ANGLE	PART NO.	SCALE:	1:1	PROJ:	SHEET
	A		NEW				10~0.25	±0.25			U-M-M5DD-W-3				1 OF 1
							5~0.10	±0.20	±2'						
							~5	±0.15							