



Pushing Performance

Han 24HPR VarioShell-4xM25-Set2



Part number	10 40 124 1002
Specification	Han 24HPR VarioShell-4xM25-Set2
HARTING eCatalogue	https://b2b.harting.com/10401241002

Identification

Category	Hoods/Housings
Series of hoods/housings	Han [®] HPR VarioShell
Type of hood/housing	Complete set
Description of hood/housing	Angled

Version

Size	24 HPR
Cable entry	for 1x 24 HPR 4x M32
Field of application	Hoods/housings for harsh outdoor environments
Details	Please note the installation manual.
Pack contents	Bulkhead mounted housing Mounting cover 1x Bulkhead mounted housing 24 HPR enlarged Fixing screws

Technical characteristics

Tightening torque	4 Nm Mounting cover 12 Nm Fixing screws 12 Nm PE screw
Limiting temperature	-40 ... +125 °C
Degree of protection acc. to IEC 60529	IP66 IP67 IP68 IP69



Pushing Performance

Material properties

Material (hood/housing)	Aluminium die-cast Corrosion resistant
Surface (hood/housing)	Powder-coated
Colour (hood/housing)	RAL 9005 (jet black)
Material (seal)	NBR
Material (locking)	Stainless steel

Specifications and approvals

CE	Yes
----	-----

Commercial data

Packaging size	1
Net weight	5,060 g
Country of origin	China
European customs tariff number	85389099
eCl@ss	27440202 Shell for industrial connectors