KODENSHI AUK


DN100S

NPN Silicon Transistor

Features

- Extremely low collector-to-emitter saturation voltage
  ($V_{CE(SAT)}$= 0.15V Typ. @I_C/I_B=400mA/20mA)
- Suitable for low voltage large current drivers
- Complementary pair with DP100S
- Switching Application

PIN Connection



Ordering Information

Type NO.	Marking	Package Code
DN100S	N03 □ ① ②	SOT-23F

① Device Code ② Year&Week Code

Absolute maximum ratings (Ta=25°C)

Characteristic	Symbol	Ratings	Unit
Collector-Base voltage	V_{CBO}	15	V
Collector-Emitter voltage	V_{CEO}	12	V
Emitter-Base voltage	V_{EBO}	5	V
Collector current	I_C	1	A
Collector dissipation	P_C	200	mW
Junction temperature	T_j	150	°C
Storage temperature	T_{stg}	-55~150	°C

Electrical Characteristics (Ta=25°C)

Characteristic	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Collector-Base breakdown voltage	BV_{CBO}	I_C=50μA, I_E=0	15	-	-	V
Collector-Emitter breakdown voltage	BV_{CEO}	I_C=1mA, I_B=0	12	-	-	V
Emitter-Base breakdown voltage	BV_{EBO}	I_E=50μA, I_C=0	5	-	-	V
Collector cut-off current	I_{CBO}	V_{CB}=12V, I_E=0	-	-	0.1	μA
Emitter cut-off current	I_{EBO}	V_{EB}=5V, I_C=0	-	-	0.1	μA
DC current gain	h_{FE1}	V_{CE}=1V, I_C=100mA	200	-	450	-
	h_{FE2}	V_{CE}=1V, I_C=1A	70	-	-	-
Collector-Emitter saturation voltage	$V_{CE(sat)}$	I_C=400mA, I_B=20mA	-	-	0.25	V
Base-Emitter saturation voltage	$V_{BE(sat)}$	I_C=400mA, I_B=20mA	-	-	1.2	V
Transition frequency	f_T	V_{CE}=5V, I_C=50mA	-	260	-	MHz
Collector output capacitance	C_{ob}	V_{CB}=10V, I_E=0, f=1MHz	-	5	-	pF

Electrical Characteristic Curves

Fig. 1 P_C - T_a




Fig. 2 I_C - V_{BE}




Fig. 3 h_{FE}-I_C






Fig. 4 $V_{CE(sat)}$-I_C




Outline Dimension



SYMBOL	MILLIMETER(mm)			NOTE
	MINIMUM	NOMINAL	MAXIMUM	
A	0.80	0.90	1.00	
A1	0.00	–	0.10	
b	0.35	0.40	0.45	
c	0.10	0.15	0.20	
D	2.80	2.90	3.00	
E	2.30	2.40	2.50	
E1	1.50	1.60	1.70	
e	0.95BSC			
e1	1.80	1.90	2.00	
L	0.48	0.58	0.68	
L1	0.30	–	0.50	

※Recommend PCB solder land [Unit: mm]



The AUK Corp. products are intended for the use as components in general electronic equipment (Office and communication equipment, measuring equipment, home appliance, etc.).

Please make sure that you consult with us before you use these AUK Corp. products in equipments which require high quality and / or reliability, and in equipments which could have major impact to the welfare of human life(atomic energy control, airplane, spaceship, transportation, combustion control, all types of safety device, etc.). AUK Corp. cannot accept liability to any damage which may occur in case these AUK Corp. products were used in the mentioned equipments without prior consultation with AUK Corp..

Specifications mentioned in this publication are subject to change without notice.