

# RF AMPLIFIER

## MODEL *TM6121*

Available as: TM6121, 4 Pin TO-8 (T4)  
 TN6121, 4 Pin Surface Mount (SM3)  
 FP6121, 4 Pin Flatpack (FP4)  
 BX6121, Connectorized Housing (H1)

### Features

- High IP3: +38 dBm Typical
- Low Noise Figure: <3 dB Typical
- Operating Temp. - 55 °C to +85 °C
- Environmental Screening Available

### Specifications

CHARACTERISTIC	TYPICAL Ta= 25 °C	MIN/MAX Ta = -55 °C to +85 °C
Frequency	20 - 200 MHz	20 - 200 MHz
Gain (dB)	10	10 ± 0.6 Min.
Power @ 1 dB Comp. (dBm)	+20	+18 Min.
Reverse Isolation (dB)	-18	-17 Max.
VSWR In	<1.75:1	2.0:1 Max.
Out	<1.75:1	2.0:1 Max.
Noise Figure (dB)	<3	4.0 Max.
Power Vdc	+15	+15
mA	60	70 Max.

Note: Care should always be taken to effectively ground the case of each unit.


### Typical Intermodulation Performance at 25 ° C

Second Order Harmonic Intercept Point ..... +60 dBm (Typ.)  
 Second Order Two Tone Intercept Point ..... +55 dBm (Typ.)  
 Third Order Two Tone Intercept Point ..... +38 dBm (Typ.)

### Maximum Ratings

Ambient Operating Temperature ..... -55°C to + 100 °C  
 Storage Temperature ..... -62°C to + 125 °C  
 Case Temperature ..... + 125 °C  
 DC Voltage ..... + 18 Volts  
 Continuous RF Input Power ..... + 17 dBm  
 Short Term RF Input Power.... 200 Milliwatts (1 Minute Max.)  
 Maximum Peak Power..... 0.5 Watt (3 µsec Max.)

### Typical Performance Data



Legend ——— + 25 °C - - - - + 85 °C ······ -55 °C

### Linear S-Parameters

FREQ. MHz	--- S11 ---		--- S21 ---		--- S12 ---		--- S22 ---	
	Mag	Deg	Mag	Deg	Mag	Deg	Mag	Deg
10	.20	-148	3.10	-174	.11	-175	.21	-169
20	.19	-166	3.12	178	.12	176	.22	-176
50	.18	176	3.09	165	.11	163	.22	176
100	.18	161	3.07	147	.11	143	.23	-165
150	.18	151	3.08	130	.11	126	.24	155
200	.20	139	3.10	112	.11	108	.24	148
300	.25	108	3.01	71	.09	78	.30	143



Spectrum Microwave · 2144 Franklin Drive N.E. · Palm Bay, Florida 32905 · PH (888) 553-7531 · Fax (888) 553-7532 6/22/04

www.spectrummicrowave.com Spectrum Microwave (Europe) · 2707 Black Lake Place · Philadelphia, Pa. 19154 · PH (215) 464-4000 · Fax (215) 464-4001