

FEATURES

- **HIGH POWER**
P1dB=33.0dBm at 5.1GHz to 7.2GHz
- **HIGH GAIN**
G1dB=22.0dB at 5.1GHz to 7.2GHz
- **BROAD BAND INTERNALLY MATCHED**
- **HERMETICALLY SEALED PACKAGE**

ABSOLUTE MAXIMUM RATINGS (Ta= 25°C)

CHARACTERISTICS	SYMBOL	UNIT	RATING
Drain Supply Voltage	VDD	V	15
Gate Supply Voltage	VGG	V	-10
Input Power	Pin	W	0.1
Flange Temperature	Tf	°C	-30 ~ +80
Storage Temperature	Tstg	°C	-65 ~ +175

RF PERFORMANCE SPECIFICATIONS (Ta= 25°C)

CHARACTERISTICS	SYMBOL	CONDITION	UNIT	MIN.	TYP.	MAX.
Output Power at 1dB Compression Point	P1dB	VDD1=VDD2=VDD3 = 10V VGG= -5V f = 5.1 – 7.2GHz	dBm	32.0	33.0	—
Power Gain at 1dB Compression Point	G1dB			dB	20.0	22.0
Gain Flatness (1)*	ΔG1		dB	—	—	±1.5
Gain Flatness (2)**	ΔG2		dB	—	—	±2.0
Drain Current***	IDD		A	—	1.60	1.90
Input VSWR	VSWRi		—	—	—	3.0

* ΔG1 at f = 5.9 – 7.2GHz


** ΔG2 at f = 5.1 – 7.2GHz

*** IDD = IDD1 + IDD2 + IDD3

◆The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA for any infringements of patents or other rights of the third parties which may results from its use. No license is granted by implication or otherwise under any patent or patent rights of TOSHIBA or others. The information contained herein is subject to change without prior notice. It is therefor advisable to contact TOSHIBA before proceeding with design of equipment incorporating this product.

TMD0507-2A

PACKAGE OUTLINE (2-11E1A)



HANDLING PRECAUTIONS FOR PACKAGED TYPE

Soldering iron should be grounded and the operating time should not exceed 10 seconds at 260°C. Flanges of devices should be attached using screws and washers. Recommended torques are 0.18-0.20 N·m.

TMD0507-2A

S-Parameters of TMD0507-2A

VDD=10V, VGG=-5V

Freq. (GHz)	S11		S21		S12		S22	
	MAG	ANG	MAG	ANG	MAG	ANG	MAG	ANG
4.9	0.05	3	18.2	-37	0.004	-22	0.54	22
5.0	0.01	-80	20.0	-72	0.004	-28	0.52	16
5.1	0.05	178	20.2	-105	0.004	-34	0.51	11
5.2	0.10	152	19.6	-135	0.004	-42	0.51	4
5.3	0.14	136	18.9	-163	0.005	-48	0.50	-4
5.4	0.18	123	18.6	170	0.005	-59	0.48	-15
5.5	0.21	112	18.5	145	0.005	-70	0.45	-29
5.6	0.24	96	19.1	119	0.005	-82	0.40	-46
5.7	0.23	77	19.4	91	0.005	-86	0.36	-63
5.8	0.22	59	19.3	63	0.004	-96	0.31	-83
5.9	0.20	38	19.0	35	0.004	-105	0.28	-106
6.0	0.17	15	18.4	8	0.004	-114	0.25	-131
6.1	0.16	-8	17.5	-19	0.004	-121	0.24	-155
6.2	0.15	-32	16.7	-45	0.004	-128	0.24	-176
6.3	0.15	-52	16.0	-71	0.003	-129	0.25	165
6.4	0.16	-67	15.5	-95	0.003	-133	0.26	151
6.5	0.17	-77	15.3	-120	0.003	-143	0.26	137
6.6	0.18	-83	15.3	-145	0.002	-145	0.27	126
6.7	0.19	-86	15.8	-171	0.002	-152	0.27	116
6.8	0.19	-87	16.8	161	0.002	-158	0.27	106
6.9	0.21	-86	18.2	131	0.002	-166	0.27	96
7.0	0.24	-88	19.8	96	0.002	-167	0.27	89
7.1	0.26	-96	20.3	56	0.001	-177	0.29	82
7.2	0.24	-103	18.3	14	0.001	-174	0.33	72
7.3	0.21	-107	15.3	-24	0.001	-163	0.36	59
7.4	0.18	-109	12.3	-61	0.001	-164	0.38	45