

Series 801 Mighty Mouse Double-Start ACME Thread Square Flange Jam Nut PCB Receptacle

801-075 Ordering Information



Rear Panel mount jam nut receptacle features square flange for secure attachement of rigid boards or flex circuits. Flange has #2-56 stainless steel helicoils and integral standoffs. PC tail contacts are facotry installed, potte with epoxy and are nonremovable. Gold–plated copper alloy contacts, aluminum or stainless steel shell, fluorosilicone seals and LCP insulators

How To Order									
Sample Part Number	801-075	-07	м	6-7	Р	Α			
Series	801-075 = Receptacle with Printed Circuit Board Contacts or Solder Cup Contacts								
Shell Style	-07 = Jam Nut								
Material and Finish	M = Aluminum / Electroless Nickel RoHS Compliant								
	MT = Aluminum / Nickel-PTFE RoHS Compliant								
	NF = Aluminum / Cadmium with Olive Drab Chromate								
	ZNU = Aluminum / Zinc-Nickel with Black Chromate								
	Z1 = Stainless Steel / Passivated RoHS Compliant								
Shell Size - Insert Arrangement	See Contact Arrangements page D-2								
Contact Type	P = Pin, PC Tail								
	S = Socket, PC Tail								
Shell Key Positions (See Table I)	A = Normal B = Pos. B C = Pos. C D = Pos. D E = Pos. F F = Pos. F								

Table I: Key Positions							
	A°	B°	-				
Α	150°	210°	A°				
В	75°	210°					
С	95°	230°					
D	140°	275°					
E	75°	275°					
F	95°	210°					

Dimensions in Inches (millimeters) are subject to change without notice.

U.S. CAGE Code 06324

 GLENAIR, INC.
 1211
 AIR
 WAY
 GLENDALE,
 CA
 91201-2497
 818-247-6000
 FAX
 818-500-9912

 www.glenair.com
 D-28
 E-Mail: sales@glenair.com

Series 80 Mighty Mouse

© 2014 Glenair, Inc.