National Semiconductor


54LS126/DM74LS126A Quad TRI-STATE® Buffers

General Description

This device contains four independent gates each of which performs a non-inverting buffer function. The outputs have the TRI-STATE feature. When enabled, the outputs exhibit the low impedance characteristics of a standard LS output with additional drive capability to permit the driving of bus lines without external resistors. When disabled, both the output transistors are turned off presenting a high-impedance state to the bus line. Thus the output will act neither as a significant load nor as a driver. To minimize the possibility that two outputs will attempt to take a common bus to opposite logic levels, the disable time is shorter than the enable time of the outputs.

Connection Diagram

Dual-In-Line Package



TL/F/6388–1

Order Number 54LS126DMQB, 54LS126FMQB, DM74LS126AM or DM74LS126AN
See NS Package Number M14A, N14A or W14B

Function Table

$Y = A$

Inputs		Output
A	C	Y
L	H	L
H	H	H
X	L	Hi-Z

H = High Logic Level

L = Low Logic Level

X = Either Low or High Logic Level

Hi-Z = TRI-STATE (Outputs are disabled)

Absolute Maximum Ratings (Note)

If Military/Aerospace specified devices are required, please contact the National Semiconductor Sales Office/Distributors for availability and specifications.

Supply Voltage	7V
Input Voltage	7V
Operating Free Air Temperature Range	
54LS	−55°C to +125°C
DM74LS	0°C to +70°C
Storage Temperature Range	−65°C to +150°C

Note: *The "Absolute Maximum Ratings" are those values beyond which the safety of the device cannot be guaranteed. The device should not be operated at these limits. The parametric values defined in the "Electrical Characteristics" table are not guaranteed at the absolute maximum ratings. The "Recommended Operating Conditions" table will define the conditions for actual device operation.*

Recommended Operating Conditions

Symbol	Parameter	54LS126			DM74LS126A			Units
		Min	Nom	Max	Min	Nom	Max	
V_{CC}	Supply Voltage	4.5	5	5.5	4.75	5	5.25	V
V_{IH}	High Level Input Voltage	2			2			V
V_{IL}	Low Level Input Voltage			0.7			0.8	V
I_{OH}	High Level Output Current			−1			−2.6	mA
I_{OL}	Low Level Output Current			12			24	mA
T_A	Free Air Operating Temperature	−55		125	0		70	°C

Electrical Characteristics over recommended operating free air temperature range (unless otherwise noted)

Symbol	Parameter	Conditions		Min	Typ (Note 1)	Max	Units
V_I	Input Clamp Voltage	V_{CC} = Min, I_I = −18 mA				−1.5	V
V_{OH}	High Level Output Voltage	V_{CC} = Min, I_{OH} = Max, V_{IH} = Min		2.4			V
V_{OL}	Low Level Output Voltage	V_{CC} = Min, I_{OL} = Max, V_{IL} = Max, V_{IH} = Min	54LS			0.4	V
			DM74		0.35	0.5	
		I_{OL} = 12 mA, V_{CC} = Min			0.25	0.4	
I_I	Input Current @ Max Input Voltage	V_{CC} = Max, V_I = 10V (54LS), V_I = 7V (DM74)				0.1	mA
I_{IH}	High Level Input Current	V_{CC} = Max, V_I = 2.7V				20	µA
I_{IL}	Low Level Input Current	V_{CC} = Max, V_I = 0.4V				−0.4	mA
I_{OZH}	Off-State Output Current with High Level Output Voltage Applied	V_{CC} = Max, V_O = 2.4V, V_{IH} = Min, V_{IL} = Max				20	µA
I_{OZL}	Off-State Output Current with Low Level Output Voltage Applied	V_{CC} = Max, V_O = 0.4V, V_{IH} = Min, V_{IL} = Max				−20	µA
I_{OS}	Short Circuit Output Current	V_{CC} = Max (Note 2)	54LS	−30		−130	mA
			DM74	−20		−100	
I_{CC}	Supply Current	V_{CC} = Max (Note 3)	DM74		12	22	mA
I_{CCL}	Supply Current	V_I = 0V	54LS			24	mA
I_{CCH}	Supply Current	V_I = 4.5V	54LS			20	mA

Note 1: All typicals are at V_{CC} = 5V, T_A = 25°C.

Note 2: Not more than one output should be shorted at a time, and the duration should not exceed one second.

Note 3: I_{CC} is measured with both the output control and data inputs grounded.

Switching Characteristics at V_{CC} = 5V and T_A = 25°C (See Section 1 for Test Waveforms and Output Load)

Symbol	Parameter	54LS		DM74LS		Units
		C_L = 50 pF		C_L = 150 pF, R_L = 667Ω		
		Min	Max	Min	Max	
t_{PLH}	Propagation Delay Time Low to High Level Output		15		21	ns
t_{PHL}	Propagation Delay Time High to Low Level Output		18		22	ns
t_{PZH}	Output Enable Time to High Level Output		30		36	ns
t_{PZL}	Output Enable Time to Low Level Output		20		42	ns
t_{PHZ}	Output Disable Time from High Level Output (Note 1)		30			ns
t_{PLZ}	Output Disable Time from Low Level Output (Note 1)		30			ns

Note 1: C_L = 5pF.