



TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,
Tao-Yuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: tstsales@mail.taisaw.com Web: www.taisaw.com

Product Specifications Approval Sheet

Product Description: SAW Resonator 1600MHz SMD 3.0X3.0 mm(300KHz)

TST Parts No.: TC0671A

Customer Parts No.: _____

Company: _____
Division: _____
Approved by : _____
Date: _____

Checked by: _____ Hong Pu Lin *Hong Pu Lin*

Approval by: _____ Andy Yu *Andy Yu*

Date: _____ 2020/02/05

1. Customer signed back is required before TST can proceed with sample build and receive orders.
2. Orders received without customer signed back will be regarded as agreement on the specifications.
3. Any specifications changes must be approved upon by both parties and a new revision of specifications shall be released to reflect the changes



TAI-SAW TECHNOLOGY CO., LTD.

No.3, Industrial 2nd Rd., Ping-Chen Industrial District, Taoyuan, Taiwan, R.O.C.

TEL: 886-3-4690038

FAX: 886-3-4697532

E-mail: tstsales3@mail.taisaw.com Web: www.taisaw.com

SAW Resonator 1600.00 MHz

MODEL NO.: TC0671A

Rev. NO. 1.0

A. MAXIMUM RATING:

1. Input Power Level: 0 dBm
2. DC voltage: 0 V
3. Operating Temperature: -40°C to +85°C
4. Storage Temperature: -40°C to +85°C
5. Moisture Sensitivity Level: Level 1(**MSL1**)

RoHS Compliant

Lead-free soldering

Electrostatic Sensitive Device

B. ELECTRICAL CHARACTERISTICS:


Characteristic	Units	Min	Type	Max
Center frequency F_c	MHz	1599.7	1600	1600.3
Insertion Loss IL	dB		0.84	2.5
Unload quality factor	-		7394	
Motional Capacitance C₁	fF		3.9018	
Motional Inductance L₁	μH		2.5366	
Motional Resistance R₁	Ohm		3.4482	
Parallel Capacitance C₀	pF		2.0104	
Frequency Temperature coefficient (TC _f)	ppm / °C	-0.05 Typ.		
Turnover To	°C		25	
Package size	mm	3.0 x 3.0		
Frequency Aging Absolute (First Year)	ppm/yr	±10		

*Frequency define by Yr(real) peak at room temperature.


Temperature dependence of fc: $fc(T_A) = fc(T_0)(1 - TC_f(T_A - T_0)^2)$

C. EQUVIRENT CIRCUIT:


One-Port Resonator:




D. FREQUENCY CHARATERISTICS:



E. TEST CIRCUIT:




F. MECHANICAL DIMENSIONS:




WK01	WK02	WK03	WK04	WK05	WK06	WK07	WK08	WK09	WK10	WK11	WK12	WK13
A	B	C	D	E	F	G	H	I	J	K	L	M
WK14	WK15	WK16	WK17	WK18	WK19	WK20	WK21	WK22	WK23	WK24	WK25	WK26
N	O	P	Q	R	S	T	U	V	W	X	Y	Z
WK27	WK28	WK29	WK30	WK31	WK32	WK33	WK34	WK35	WK36	WK37	WK38	WK39
a	b	c	d	e	f	g	h	i	j	k	l	m
WK40	WK41	WK42	WK43	WK44	WK45	WK46	WK47	WK48	WK49	WK50	WK51	WK52
n	o	p	q	r	s	t	u	v	w	x	y	z

G. PCB FOOTPRINT:




H. PACKING:

1. REEL DIMENSION (Please refer to FR-75D10 for packing quantity)



2. TAPE DIMENSION



I. RECOMMENDED REFLOW PROFILE:

1. Preheating shall be fixed at 150~180°C for 60~90 seconds.
2. Ascending time to preheating temperature 150°C shall be 30 seconds min.
3. Heating shall be fixed at 220°C for 50~80 seconds and at 260°C +0/-5°C peak (20~40sec).
4. Time: 2 times.

