LCY W5SM

Golden DRAGON®



Applications

- Signalling

Features:

- Package: white SMT package, colored diffused silicone resin
- Chip technology: ThinGaN
- Typ. Radiation: 120° (Lambertian emitter)
- Color: Cx = 0.56, Cy = 0.42 acc. to CIE 1931 (• converted yellow)
- Optical efficacy: 50 lm/W
- Corrosion Robustness Class: 3B
- ESD: 8 kV acc. to ANSI/ESDA/JEDEC JS-001 (HBM, Class 3B)

Not for new design

Ordering Information

Type	Luminous Flux [1] I_F = 350 mA Φ_V	Ordering Code
LCY W5SM-HZJZ-5E-1	39 ... 71 lm	Q65111A2605

Not for new design

Maximum Ratings

Parameter	Symbol		Values
Operating Temperature	T_{op}	min. max.	-40 °C 125 °C
Storage Temperature	T_{stg}	min. max.	-40 °C 125 °C
Junction Temperature	T_j	max.	135 °C
Junction Temperature for short time applications*	T_j	max.	150 °C
Forward Current T_S = 25 °C	I_F	min. max.	100 mA 500 mA
Surge Current t ≤ 10 µs; D = 0.005 ; T_S = 25 °C	I_{FS}	max.	2500 mA
ESD withstand voltage acc. to ANSI/ESDA/JEDEC JS-001 (HBM, Class 3B)	V_{ESD}		8 kV
Reverse current [2)]	I_R	max.	200 mA

*The median lifetime (L70/B50) for Tj =150°C is 100h.

Not for new design

Characteristics

I_F = 350 mA; T_S = 25 °C

Parameter	Symbol		Values
Chromaticity Coordinate [3]	Cx	typ.	0.56
	Cy	typ.	0.42
Viewing angle at 50 % I_V	2φ	typ.	120 °
Forward Voltage [4] I_F = 350 mA	V_F	min.	2.80 V
		typ.	3.20 V
		max.	3.60 V
Reverse voltage (ESD device)	$V_{R\ ESD}$	min.	45 V
Reverse voltage [2] I_R = 20 mA	V_R	max.	1.2 V
Real thermal resistance junction/solderpoint [5]	$R_{thJS\ real}$	typ.	5.0 K / W
		max.	6.4 K / W

Not for new design

Brightness Groups


Group	Luminous Flux [1] I_F = 350 mA min. Φ_V	Luminous Flux [1] I_F = 350 mA max. Φ_V	Luminous Intensity [6] I_F = 350 mA typ. I_v
HZ	39 lm	45 lm	14 cd
JX	45 lm	52 lm	16 cd
JY	52 lm	61 lm	19 cd
JZ	61 lm	71 lm	22 cd

Forward Voltage Groups

Group	Forward Voltage [4] I_F = 350 mA min. V_F	Forward Voltage [4] I_F = 350 mA max. V_F
24	2.80 V	3.00 V
64	3.00 V	3.20 V
A4	3.20 V	3.40 V
E4	3.40 V	3.60 V

Not for new design

Chromaticity Coordinate Groups [3)]



Color Chromaticity Groups

Group	Cx	Cy
5E	0.5536	0.4221
	0.5705	0.4289
	0.5883	0.4111
	0.5764	0.4075

Not for new design

Group Name on Label


Example: HZ-5E-24

Brightness	Color chromaticity	Forward Voltage
HZ	5E	24

Not for new design


Relative Spectral Emission [6]

$I_{rel} = f(\lambda)$; I_F = 350 mA; T_S = 25 °C



Radiation Characteristics [6]


$I_{rel} = f(\phi)$; T_S = 25 °C



Not for new design


Forward current [6), 7)]

$I_F = f(V_F)$; T_S = 25 °C




Relative Luminous Flux [6), 7)]

$\Phi_v/\Phi_v(350\ mA) = f(I_F)$; T_S = 25 °C



Chromaticity Coordinate Shift [6)]


$\Delta Cx, \Delta Cy = f(I_F)$; T_S = 25 °C



Not for new design


Forward Voltage [6)]

$\Delta V_F = V_F - V_F(25\ °C) = f(T_j)$; I_F = 350 mA




Relative Luminous Flux [6)]

$\Phi_v/\Phi_v(25\ °C) = f(T_j)$; I_F = 350 mA



Chromaticity Coordinate Shift [6)]


$\Delta Cx, \Delta Cy = f(T_j)$; I_F = 350 mA



Not for new design


Max. Permissible Forward Current

$I_F = f(T)$




Permissible Pulse Handling Capability

$I_F = f(t_p)$; D: Duty cycle



Not for new design


Dimensional Drawing [8)]



Approximate Weight:	218.0 mg
Package marking:	Cathode
Corrosion test:	Class: 3B Test condition: 40°C / 90 % RH / 15 ppm H_2S / 14 days (stricter then IEC 60068-2-43)
ESD advice:	LED is protected by ESD device which is connected in paralell to LED-Chip.

Not for new design

Recommended Solder Pad [8)]




For superior solder joint connectivity results we recommend soldering under standard nitrogen atmosphere. Package not suitable for ultra sonic cleaning.

Not for new design

Reflow Soldering Profile

Product complies to MSL Level 2 acc. to JEDEC J-STD-020E




Profile Feature	Symbol	Pb-Free (SnAgCu) Assembly			Unit
		Minimum	Recommendation	Maximum	
Ramp-up rate to preheat*) 25 °C to 150 °C			2	3	K/s
Time t_S T_{Smin} to T_{Smax}	t_S	60	100	120	s
Ramp-up rate to peak*) T_{Smax} to T_P			2	3	K/s
Liquidus temperature	T_L		217		°C
Time above liquidus temperature	t_L		80	100	s
Peak temperature	T_P		245	260	°C
Time within 5 °C of the specified peak temperature T_P - 5 K	t_P	10	20	30	s
Ramp-down rate* T_P to 100 °C			3	6	K/s
Time 25 °C to T_P				480	s

All temperatures refer to the center of the package, measured on the top of the component
* slope calculation DT/Dt: Dt max. 5 s; fulfillment for the whole T-range


Not for new design

Taping [8)]



Not for new design

Tape and Reel [9)]




Leader: min. 400mm*
Trailer: min. 160mm*
*)Dimensions acc. to IEC 60286-3; EIA 481-E

Reel dimensions [mm]


A	W	N_{min}	W_1	$W_{2\,max}$	Pieces per PU
180 mm	24 + 0.3 / - 0.1	60/100	24.4 + 2	30.4	800

Not for new design

Barcode-Product-Label (BPL)




Dry Packing Process and Materials [8)]



Moisture-sensitive product is packed in a dry bag containing desiccant and a humidity card according JEDEC-STD-033.

Not for new design

Transportation Packing and Materials [8)]




Dimensions of transportation box in mm

Width	Length	Height
195 ± 5 mm	195 ± 5 mm	42 ± 5 mm

Not for new design

Type Designation System



Not for new design

Notes

The evaluation of eye safety occurs according to the standard IEC 62471:2006 (photo biological safety of lamps and lamp systems). Within the risk grouping system of this IEC standard, the LED specified in this data sheet fall into the class **exempt group (exposure time 10000 s)**. Under real circumstances (for exposure time, eye pupils, observation distance), it is assumed that no endangerment to the eye exists from these devices. As a matter of principle, however, it should be mentioned that intense light sources have a high secondary exposure potential due to their blinding effect. As is also true when viewing other bright light sources (e.g. headlights), temporary reduction in visual acuity and afterimages can occur, leading to irritation, annoyance, visual impairment, and even accidents, depending on the situation.

Subcomponents of this LED contain, in addition to other substances, metal filled materials including silver. Metal filled materials can be affected by environments that contain traces of aggressive substances. Therefore, we recommend that customers minimize LED exposure to aggressive substances during storage, production, and use. LEDs that showed visible discoloration when tested using the described tests above did show no performance deviations within failure limits during the stated test duration. Respective failure limits are described in the IEC60810.

For further application related informations please visit www.osram-os.com/appnotes

Not for new design

Disclaimer

Disclaimer
Language english will prevail in case of any discrepancies or deviations between the two language wordings.

Attention please!
The information describes the type of component and shall not be considered as assured characteristics.
Terms of delivery and rights to change design reserved. Due to technical requirements components may contain dangerous substances.
For information on the types in question please contact our Sales Organization.
If printed or downloaded, please find the latest version on the OSRAM OS webside.

Packing
Please use the recycling operators known to you. We can also help you – get in touch with your nearest sales office.
By agreement we will take packing material back, if it is sorted. You must bear the costs of transport. For packing material that is returned to us unsorted or which we are not obliged to accept, we shall have to invoice you for any costs incurred.

Product safety devices/applications or medical devices/applications
OSRAM OS components are not developed, constructed or tested for the application as safety relevant component or for the application in medical devices.

In case Buyer – or Customer supplied by Buyer– considers using OSRAM OS components in product safety devices/applications or medical devices/applications, Buyer and/or Customer has to inform the local sales partner of OSRAM OS immediately and OSRAM OS and Buyer and /or Customer will analyze and coordinate the customer-specific request between OSRAM OS and Buyer and/or Customer.

Not for new design

Glossary

1) **Brightness**: Brightness values are measured during a current pulse of typically 25 ms, with an internal reproducibility of ±8 % and an expanded uncertainty of ±11 % (acc. to GUM with a coverage factor of k = 3).

2) **Reverse Operation**: Reverse Operation of 10 hours is permissible in total. Continuous reverse operation is not allowed.

3) **Chromaticity coordinate groups**: Chromaticity coordinates are measured during a current pulse of typical 25 ms, with an internal reproducibility of +/- 0.001 and an expanded uncertainty of +/- 0.004 (acc. to GUM with a coverage factor of k = 3).

4) **Forward Voltage**: Forward voltages are tested at a current pulse duration of 1 ms and a tolerance of ±0.05 V and an expanded uncertainty of ±0.1 V (acc. to GUM with a coverage factor of k=3).

5) **Thermal Resistance**: Rth max is based on statistic values (6σ).

6) **Typical Values**: Due to the special conditions of the manufacturing processes of LED, the typical data or calculated correlations of technical parameters can only reflect statistical figures. These do not necessarily correspond to the actual parameters of each single product, which could differ from the typical data and calculated correlations or the typical characteristic line. If requested, e.g. because of technical improvements, these typ. data will be changed without any further notice.

7) **Characteristic curve**: In the range where the line of the graph is broken, you must expect higher differences between single LEDs within one packing unit.

8) **Tolerance of Measure**: Unless otherwise noted in drawing, tolerances are specified with ±0.1 and dimensions are specified in mm.

9) **Tape and Reel**: All dimensions and tolerances are specified acc. IEC 60286-3 and specified in mm.

Not for new design

Published by OSRAM Opto Semiconductors GmbH
Leibnizstraße 4, D-93055 Regensburg
www.osram-os.com © All Rights Reserved.

EU RoHS and China RoHS compliant product

此产品符合欧盟 RoHS 指令的要求；
按照中国的相关法规和标准，不含有毒有害物质或元素。

Not for new design

OSRAM
Opto Semiconductors