

PJQA6V8C

ESD Protection diode

VOLTAGE	5.0 Volts	POEWR	150 Watts
----------------	------------------	--------------	------------------

FEATURES

- ESD Protection
- Small mold type
- Silicon epitaxial planar
- In compliance with EU RoHS 2002/95/EC directives


MECHANICAL DATA

Case: SOT23-6L Molded plastic

Terminals: Solder plated, solderable per MIL-STD-750, Method 2026

SOT23-6L

Unit: inch (mm)







ABSOLUTE MAXIMUM RATINGS (TA=25°C)

Parameter	Symbol	Limits	Unit
Power dissipation	P	200	mW
Peak Pulse Power-1(tp=10 x 1000us)	PPK	30	mW
Peak Pulse Power-2(tp=8 x 20us)	PPK	150	mW
Junction temperature	TJ	150	°C
Storage temperature	TSTG	-55 to + 150	°C

ELECTRICAL CHARACTERISTICS (TA=25°C)

Parameter	Symbol	Min	Typ	Max	Unit	Conditions
Zener voltage	V _Z	6.1	-	7.2	V	I _Z = 1mA
Reverse current	I _R	-	-	1	μA	V _R = 5.0V
Forward current	V _F	-	-	1.25	V	I _F = 200mA
Junction capacitance	C _T	-	-	240	pF	V _R = 0V, f = 1MHz

PJQA6V8C




PJQA6V8C

MOUNTING PAD LAYOUT

SOT23-6L

Unit: inch (mm)



ORDER INFORMATION

- Packing information
 - T/R - 10K per 13" plastic Reel
 - T/R - 3K per 7" plastic Reel

LEGAL STATEMENT

Copyright PanJit International, Inc 2009

The information presented in this document is believed to be accurate and reliable. The specifications and information herein are subject to change without notice. Pan Jit makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose. Pan Jit products are not authorized for use in life support devices or systems. Pan Jit does not convey any license under its patent rights or rights of others.