



Function Description

This part is a coaxial cable assembly for telecommunication equipment. It consists of 1/4" super flexible coaxial cable with PE jacket, one 7-16 r/a male and one 4.3-10 r/a male connector. The assembly is waterproof in mated condition and UV protected.

Available Variants

The assembly is available in lengths from 0.5 m to 10 m in intervals of 0.5 m. Different feet length are available on request.

Assembly Parts

Connector	7-16 r/a male & 4.3-10 r/a male (type1) connector plated with white bronze
Cable	S-Link 1/4"S, PE jacket
Marking 1	Direct print onto the cable or one wrapping label Marking includes manufacturer, part nr. & batch no.
Marking 2	Direct print onto the cable or on wrapping label Marking includes "Rosenberger factory made" Position in the middle of the cable
Bend Protection	molding material PE compound

Dieses Dokument ist urheberrechtlich geschützt • This document is protected by copyright • Rosenberger Hochfrequenztechnik GmbH & Co. KG

RF_35/05.10/6.0

1/4" JUMPER

7-16 R/A MALE /
4.3-10 R/A MALE

SLJ14SP-60R64R-X-00

Electrical Data

Impedance	50 Ω
Frequency	DC to 2.7 GHz
Return loss	
DC – 1 GHz	≥ 32 dB
1 – 2.2 GHz	≥ 30 dB
2.2 – 2.7 GHz	≥ 28 dB
Insertion loss typ.	
DC – 1 GHz	≤ 0.20 dB/m (cable) + 0.01 dB * √f (GHz)
1 – 2.2 GHz	≤ 0.30 dB/m (cable) + 0.01 dB * √f (GHz)
2.2 – 2.7 GHz	≤ 0.34 dB/m (cable) + 0.01 dB * √f (GHz)
Intermodulation (3rd order @ 2 x 20 W)	typ. max.
	≤ -120 dBm ≤ -117 dBm
Relative Velocity of Propagation	83 %
DC breakdown voltage	2000 V

Mechanical Data

Coupling torque 7-16 (recommended)	25 to 30 Nm
Coupling torque 4.3-10 (recommended)	5 to 8 Nm
Spanner flat on coupling nut 7-16	32 mm
Spanner flat on coupling nut 4.3-10	22 mm
Cable diameter, jacket	7.7 mm typ.
Tensile strength	500 N
Recommended hanger spacing	0.6 m
Minimum bend radius single	13 mm*
Minimum bend radius repeated	25 mm*
*Bending starts behind connector incl. the kink protection	

Environmental Data

Operation temperature range	-40 °C to +80 °C
Installation temperature range	-25 °C to +60 °C
Degree of protection	IEC 60529, IP68 1 bar for 1 h (mated)
RoHS	compliant

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Draft	Date	Approved	Date	Rev.	Engineering change number	Name	Date
A. Gasteiger	09.03.16	M. Wimmer	17.03.2016	100	16-v083	Fl. Öllerer	17.03.2016
Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O.Box 1260 D-84526 Tittmoning Germany www.rosenberger.de						Tel. : +49 8684 18-0 Email : info@rosenberger.de	
							Page 2 / 2

Dieses Dokument ist urheberrechtlich geschützt • This document is protected by copyright • Rosenberger Hochfrequenztechnik GmbH & Co. KG

RF_35/05_10/6.0