

TSC5302D

High Voltage NPN Transistor with Diode

TO-251 (IPAK)



TO-252 (DPAK)



Pin Definition:
1. Base
2. Collector
3. Emitter


PRODUCT SUMMARY

BV_{CEO}	400V
BV_{CBO}	700V
I_C	2A
$V_{CE(SAT)}$	1.1V @ I_C=1A, I_B=0.25A

Features

- Build-in Free-wheeling Diode Makes Efficient Anti-saturation Operation
- No Need to Interest h_{FE} Value Because of Low Variable Storage-time Spread Even Though Comer Spirit Product.
- Low Base Drive Requirement
- Suitable for Half Bridge Light Ballast Application

Block Diagram



Structure

- Silicon Triple Diffused Type
- NPN Silicon Transistor with Diode

Ordering Information

Part No.	Package	Packing
TSC5302DCP ROG	TO-252	2.5kpcs / 13” Reel
TSC5302DCH C5G	TO-251	75pcs / Tube

Note: “G” denote for Halogen Free Product

Absolute Maximum Ratings (Ta = 25°C unless otherwise noted)

Parameter		Symbol	Limit	Unit
Collector-Base Voltage		V_{CBO}	700	V
Collector-Emitter Voltage		V_{CEO}	400	V
Emitter-Base Voltage		V_{EBO}	10	V
Collector Current		I_C	2	A
Collector Peak Current (tp <5ms)		I_{CM}	4	A
Base Current		I_B	1	A
Base Peak Current (tp <5ms)		I_{BM}	2	A
Total Dissipation @ Tc ≤ 25°C	TO-251	P_{tot}	1.5	W
	TO-252		25	
Maximum Operating Junction Temperature		T_J	+150	°C
Storage Temperature Range		T_{STG}	-65 to +150	°C

Thermal Performance

Parameter	Symbol	Limit	Unit
Junction to Case Thermal Resistance	$R\Theta_{JC}$	6.25	°C/W
Junction to Ambient Thermal Resistance	$R\Theta_{JA}$	100	°C/W

TSC5302D
High Voltage NPN Transistor with Diode

Electrical Specifications (Ta = 25°C unless otherwise noted)

Parameter	Conditions	Symbol	Min	Typ	Max	Unit
Static						
Collector-Base Voltage	I_C = 1mA, I_B = 0	BV_{CBO}	700	--	--	V
Collector-Emitter Breakdown Voltage[a]	I_C = 10mA, I_E = 0	BV_{CEO}	400	--	--	V
Emitter-Base Breakdown Voltage	I_E = 1mA, I_C = 0	BV_{EBO}	10	--	--	V
Collector Cutoff Current	V_{CB} = 700V, I_E = 0	I_{CBO}	--	--	1	μA
Emitter Cutoff Current	V_{EB} = 9V, I_C = 0	I_{EBO}	--	--	1	μA
Collector-Emitter Saturation Voltage[a]	I_C =0.5A, I_B =0.1A	$V_{CE(SAT)1}$	--	--	0.5	V
	I_C =1A, I_B =0.25A	$V_{CE(SAT)2}$	--	1.1	1.5	
Base-Emitter Saturation Voltage[a]	I_C =0.5A, I_B =0.1A	$V_{BE(SAT)1}$	--	--	1.1	V
	I_C =1A, I_B =0.25A	$V_{BE(SAT)2}$	--	--	1.2	
DC Current Gain	V_{CE} =5V, I_C =10mA	h_{FE} 1	10	--	--	
	V_{CE} =5V, I_C =400mA	h_{FE} 2	10	--	30	
	V_{CE} =5V, I_C =1A	h_{FE} 3	5	--	--	
Turn On Time	V_{CC} =250V, I_C =1A, I_{B1}=I_{B2} =0.2A, t_p =25μs Duty Cycle<1%	t_{ON}	--	0.15	0.3	μs
Storage Time		t_{STG}	--	0.5	0.9	μs
Fall Time		t_f	--	0.2	0.4	μs
Diode						
Fall Time	I_C =1A	t_F	--	--	800	μs
Forward Voltage Drop	I_C =1A	Vf	--	--	1.4	V

Notes: Pulsed duration = 300μs, duty cycle ≤2%

TSC5302D
High Voltage NPN Transistor with Diode

Electrical Characteristics Curve (Ta = 25°C, unless otherwise noted)

Figure 1. Static Characteristics




Figure 2. DC Current Gain




Figure 3. Vce(sat) vs. Vbe(sat)




Figure 4. Power Derating




Figure 5. Reverse Bias SOA






Figure 6. Safe Operating Area




TSC5302D
High Voltage NPN Transistor with Diode

TO-251 Mechanical Drawing



Unit: Millimeters


Marking Diagram



Y = Year Code
M = Month Code for Halogen Free Product
(**O**=Jan, **P**=Feb, **Q**=Mar, **R**=Apl, **S**=May, **T**=Jun, **U**=Jul, **V**=Aug, **W**=Sep, **X**=Oct, **Y**=Nov, **Z**=Dec)
L = Lot Code


TSC5302D
High Voltage NPN Transistor with Diode

TO-252 Mechanical Drawing



Unit: Millimeters

Marking Diagram



Y = Year Code
M = Month Code for Halogen Free Product
(**O**=Jan, **P**=Feb, **Q**=Mar, **R**=Apl, **S**=May, **T**=Jun, **U**=Jul, **V**=Aug, **W**=Sep, **X**=Oct, **Y**=Nov, **Z**=Dec)
L = Lot Code

Notice

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.