

## Features

- Saturated Output Power: +41 dBm
- Linear Gain: 24 dB
- Power Added Efficiency: 30% at  $P_{SAT}$
- 50  $\Omega$  Input / Output Match
- Ceramic Flange Mount Package
- RoHS\* Compliant and 260°C Re-flow Compatible

## Description

The MAAP-010168 is a two stage MMIC power amplifier designed for broadband high power applications. It can be used as either a driver or an output stage amplifier. This device is fully matched input and output to 50  $\Omega$  which eliminates any sensitive external RF tuning components.

The device is packaged in a lead free 10-lead flanged package for high volume manufacturing.


The MAAP-010168 is fabricated using a high reliability pHEMT process, to realize good power added efficiency and gain. The pHEMT process features full passivation for high performance and reliability.

## Ordering Information<sup>1</sup>

Part Number	Package
MAAP-010168-000000	Bulk

1. Reference Application Note M567 for package handling and mounting procedure.

## Functional Schematic



## Pin Configuration<sup>2</sup>

Pin No.	Function
1	$V_{GG2}$
2	$V_{GG1}$
3	RF Input
4	$V_{GG1}$
5	$V_{GG2}$
6	$V_{DD1}$
7	$V_{DD2}$
8	RF Output
9	$V_{DD2}$
10	$V_{DD1}$

2. Flange is DC and RF ground.

## Handling Procedures

Please observe the following precautions to avoid damage:

## Static Sensitivity

Gallium Arsenide Integrated Circuits are sensitive to electrostatic discharge (ESD) and can be damaged by static electricity. Proper ESD control techniques should be used when handling these devices.

\* Restrictions on Hazardous Substances,  
European Union Directive 2002/95/EC.

## 10 W Power Amplifier 0.5 - 3 GHz

Rev. V2

### Electrical Specifications:

Freq. = 0.5 - 3.0 GHz,  $V_{DD} = 10\text{ V}$ ,  $I_{DQ} = 3.5\text{ A}$ ,  $T_A = 25\text{ }^\circ\text{C}$ ,  $Z_0 = 50\text{ }\Omega$


Parameter	Test Conditions	Units	Min.	Typ.	Max.
Gain	Small signal	dB	19	24	—
Input Return Loss	—	dB	—	10	—
Output Return Loss	—	dB	—	10	—
P1dB	—	dBm	—	39	—
$P_{SAT}$	—	dBm	38	41	—
Current	$I_{DQ}$ $P_{SAT}$	A	— —	3.5 5.5	— —
PAE	$P_{SAT}$	%	—	30	—
Gate Bias	—	V	—	-0.7	—
Duty Cycle	—	%	—	—	100

### Absolute Maximum Ratings<sup>3,4,5</sup>

Parameter	Absolute Maximum
Input Power	+24 dBm
Operating Supply Voltage	+11 Volts
Operating Gate Voltage	-2 Volts
Operating Temperature	-40°C to +85°C
Channel Temperature <sup>6</sup>	+150°C
Storage Temperature	-65°C to +150°C

- Exceeding any one or combination of these limits may cause permanent damage to this device.
- M/A-COM Technology Solutions does not recommend sustained operation near these survivability limits.
- Operating at nominal conditions with  $T_J \leq +150\text{ }^\circ\text{C}$  will ensure  $MTTF > 1 \times 10^6$  hours.
- Junction Temperature ( $T_J$ ) =  $T_C + \theta_{JC} * ((V * I) - (P_{OUT} - P_{IN}))$   
Typical thermal resistance ( $\theta_{JC}$ ) = 2.0°C/W
  - For  $T_C = 25\text{ }^\circ\text{C}$  @ 1.5 GHz  
 $T_J = +80\text{ }^\circ\text{C}$  @ +10 V, 4 A,  $P_{OUT} = 41\text{ dBm}$ ,  $P_{IN} = 21\text{ dBm}$
  - For  $T_C = 85\text{ }^\circ\text{C}$  @ 1.5 GHz  
 $T_J = +138\text{ }^\circ\text{C}$  @ +10 V, 3.9 A,  $P_{OUT} = 41\text{ dBm}$ ,  $P_{IN} = 21\text{ dBm}$

### Recommended Bias Configuration




### Operating the MAAP-010168

The MAAP-010168 is static sensitive. Please handle with care. To operate the device, follow these steps. Ramp down or shutdown in reverse order (gate bias on first and off last). All  $V_{GG}$  pins should have the same voltage applied at all times.


- Apply  $V_{GG}$  (-1.5 V).
- Apply  $V_{DD}$  (10.0 V Typical).
- Set  $I_{DQ}$  by adjusting  $V_{GG}$ .
- Apply  $RF_{IN}$ .

## Typical Performance Curves


**Gain**




**Input Return Loss**




**Output Return Loss**




**Reverse Isolation**



**Output Power (dBm)**




**Output Power (W)**




## Typical Performance Curves


**Power Gain**




**Output Power Sweep @ 0.7 GHz**




**Power Added Efficiency**




**Output Power Sweep @ 1.5 GHz**



**Drain Current**




**Output Power Sweep @ 2.5 GHz**




## Typical Performance Curves


**Power Gain vs. Input Power @ 0.7 GHz**




**Power Gain vs. Output Power @ 0.7 GHz**




**Power Gain vs. Input Power @ 1.5 GHz**




**Power Gain vs. Output Power @ 1.5 GHz**



**Power Gain vs. Input Power @ 2.5 GHz**




**Power Gain vs. Output Power @ 2.5 GHz**




## Typical Performance Curves

**Max. Power Dissipation vs. Base Plate Temperature<sup>7</sup>**




**Junction Temperature vs. Base Plate Temperature with 50 W Power Dissipation**



7. Power dissipation should not exceed the maximum plot shown above to maintain  $T_J < 150^\circ\text{C}$ . It is recommended to monitor power dissipation and decrease power dissipation in the device as required.

## Ceramic Flange Mount Package<sup>†</sup>



<sup>†</sup> Reference Application Note M538 for lead-free solder reflow recommendations.

This is a high frequency, low thermal resistance package. The package consists of a cofired ceramic construction with a copper-tungsten base and iron-nickel-cobalt leads. The finish consists of electrolytic gold over nickel plate.

M/A-COM Technology Solutions Inc. All rights reserved.

Information in this document is provided in connection with M/A-COM Technology Solutions Inc ("MACOM") products. These materials are provided by MACOM as a service to its customers and may be used for informational purposes only. Except as provided in MACOM's Terms and Conditions of Sale for such products or in any separate agreement related to this document, MACOM assumes no liability whatsoever. MACOM assumes no responsibility for errors or omissions in these materials. MACOM may make changes to specifications and product descriptions at any time, without notice. MACOM makes no commitment to update the information and shall have no responsibility whatsoever for conflicts or incompatibilities arising from future changes to its specifications and product descriptions. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document.

THESE MATERIALS ARE PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, RELATING TO SALE AND/OR USE OF MACOM PRODUCTS INCLUDING LIABILITY OR WARRANTIES RELATING TO FITNESS FOR A PARTICULAR PURPOSE, CONSEQUENTIAL OR INCIDENTAL DAMAGES, MERCHANTABILITY, OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT. MACOM FURTHER DOES NOT WARRANT THE ACCURACY OR COMPLETENESS OF THE INFORMATION, TEXT, GRAPHICS OR OTHER ITEMS CONTAINED WITHIN THESE MATERIALS. MACOM SHALL NOT BE LIABLE FOR ANY SPECIAL, INDIRECT, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, INCLUDING WITHOUT LIMITATION, LOST REVENUES OR LOST PROFITS, WHICH MAY RESULT FROM THE USE OF THESE MATERIALS.

MACOM products are not intended for use in medical, lifesaving or life sustaining applications. MACOM customers using or selling MACOM products for use in such applications do so at their own risk and agree to fully indemnify MACOM for any damages resulting from such improper use or sale.

7

---

*M/A-COM Technology Solutions Inc. and its affiliates reserve the right to make changes to the product(s) or information contained herein without notice.*  
Visit [www.macom.com](http://www.macom.com) for additional data sheets and product information.

- **North America** Tel: 800.366.2266 / Fax: 978.366.2266
- **Europe** Tel: 44.1908.574.200 / Fax: 44.1908.574.300
- **Asia/Pacific** Tel: 81.44.844.8296 / Fax: 81.44.844.8298