# SENSITRON SEMICONDUCTOR

LED-3926 LED-3927 LED-3928

TECHNICAL DATA DATA SHEET 568, REV. -



LED Array




Sensitron provides custom light or switching LED Arrays to satisfy many electrical and mechanical design requirements. Available from 4 to 88 LEDs per array.

## **Applications/Markets:**

- τ Aircraft Switch Panels
- $\boldsymbol{\tau}$  Satellites
- $\tau$  Military
- $\tau$  Space/Aerospace
- $\tau$  High-Rel Industrial
- Input Voltages 10 to 50 Volts.
- Internal switching frequency 80kHz
- Light adjustable for day & night Brightness.
- Current 5mA to 750mA (dependant upon number of LEDs in array); high efficiency.
- Size 12 LED array is approximately 0.35" x 0.75".
- Weight 12 LED array is approximately 2.2 grams.
- Temperature range --  $-40^{\circ}$  to  $+85^{\circ}$ C.
- Available in 4 different colors:
  - -LED-3926 Red -LED-3927 White/Green -LED-3928 Amber

## **Features/Benefits:**

- $\tau$  Flexible Design Configurations
- $\tau$  Various Power Device Options



Contact the factory for your unique design requirements.

221 West Industry Court Deer Park, NY 11729-4681 Phone (631) 586 7600 Fax (631) 242 9798 
 World Wide Web - http://www.sensitron.com • E-Mail Address - sales@sensitron.com •



#### **TECHNICAL DATA**

#### DISCLAIMER:

1- The information given herein, including the specifications and dimensions, is subject to change without prior notice to improve product characteristics. Before ordering, purchasers are advised to contact the Sensitron Semiconductor sales department for the latest version of the datasheet(s).

2- In cases where extremely high reliability is required (such as use in nuclear power control, aerospace and aviation, traffic equipment, medical equipment, and safety equipment), safety should be ensured by using semiconductor devices that feature assured safety or by means of users' fail-safe precautions or other arrangement.

3- In no event shall Sensitron Semiconductor be liable for any damages that may result from an accident or any other cause during operation of the user's units according to the datasheet(s). Sensitron Semiconductor assumes no responsibility for any intellectual property claims or any other problems that may result from applications of information, products or circuits described in the datasheets.
4- In no event shall Sensitron Semiconductor be liable for any failure in a semiconductor device or any secondary damage resulting from use at a value exceeding the absolute maximum rating.

5- No license is granted by the datasheet(s) under any patents or other rights of any third party or Sensitron Semiconductor.
6- The datasheet(s) may not be reproduced or duplicated, in any form, in whole or part, without the expressed written permission of Sensitron Semiconductor.

7- The products (technologies) described in the datasheet(s) are not to be provided to any party whose purpose in their application will hinder maintenance of international peace and safety nor are they to be applied to that purpose by their direct purchasers or any third party. When exporting these products (technologies), the necessary procedures are to be taken in accordance with related laws and regulations.