

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [0901471205](#)
Status: **Active**
Overview: [cgrid_sl_products](#)
Description: 2.54mm (.100") Pitch C-Grid® PC Board Connector, Single Row, Vertical, 5 Circuits

Documents:
[3D Model](#) [RoHS Certificate of Compliance \(PDF\)](#)
[Drawing \(PDF\)](#)

Agency Certification

CSA LR19980
UL E29179

General

Product Family PCB Receptacles
Series [90147](#)
Application Board-to-Board
Overview [cgrid_sl_products](#)
Product Name C-Grid®

Physical

Circuits (Loaded) 5
Color - Resin Black
Flammability 94V-0
Glow-Wire Compliant No
Guide to Mating Part No
Keying to Mating Part None
Lock to Mating Part No
Material - Metal Phosphor Bronze
Material - Plating Mating Gold
Material - Plating Termination Tin
Material - Resin Polyester
Number of Rows 1
Orientation Vertical
PC Tail Length (in) 0.114 In
PC Tail Length (mm) 2.90 mm
PCB Locator No
PCB Retention Yes
PCB Thickness Recommended (in) 0.062 In
PCB Thickness Recommended (mm) 1.60 mm
Packaging Type Tube
Pitch - Mating Interface (in) 0.100 In
Pitch - Mating Interface (mm) 2.54 mm
Plating min: Mating (µin) 15.2
Plating min: Mating (µm) 0.38
Plating min: Termination (µin) 120
Plating min: Termination (µm) 3
Polarized to PCB No
Temperature Range - Operating -55°C to +125°C
Termination Interface: Style Through Hole

Electrical

Current - Maximum per Contact 3A
Grounding to PCB No
Voltage - Maximum 350V

Solder Process Data




image - Reference only

EU RoHS
ELV and RoHS
Compliant
REACH SVHC
Contains SVHC: No
Halogen-Free
Status
Not Reviewed

China RoHS



Need more information on product environmental compliance?

Email productcompliance@molex.com
For a multiple part number RoHS Certificate of Compliance, [click here](#)

Please visit the [Contact Us](#) section for any non-product compliance questions.

Search Parts in this Series
[90147Series](#)

Mates With
[90120](#) , [90121](#)

Use With
[90120](#) , [90121](#)

Lead-free Process Capability

Wave Capable (TH only)

Material Info

Reference - Drawing Numbers



Sales Drawing

SDA-90147


This document was generated on 05/22/2010

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

10 9 8 7 6 5 4 3 2 1



RECOMMENDED P.C. BOARD
HOLE PATTERN
FOR STRAIGHT PINS.



SECTION C-C SHOWING
STRAIGHT PINS.

NOTES:

- 1) CONTACT-PLATED PHOSPHOR BRONZE.
- 2) HOUSING-15% GLASS FILLED POLYESTER.
COLOUR: BLACK.
- 3) FOR (0.635)/.025 SQ. MALE PINS THE LENGTH
MUST BE (5.65)/.222 MIN & (7.00)/.276 MAX. TO
ENSURE GOOD CONNECTION WITH CONTACT.
- 4) PRODUCT SPECIFICATION: PS-99020-0001
- 5) PCB THICKNESS 1.6MM

ADDED GATE AREA EC NO: E2009-0250 2008/12/08 DRWN:BMAGUIRE 2008/12/08 CHKD: 2008/12/08 APPR:BMAGUIRE 2008/12/08 AC	REV	DESCRIPTION	QUALITY SYMBOLS ▼=0 ▽=0	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM/IN		SCALE 1:1	DESIGN UNITS METRIC	 THIRD ANGLE PROJECTION	
				4 PLACES	± ---	± ---	DRAWN BY DB	DATE 1987/07/14	TITLE C-GRID III, SINGLE ROW VERTICAL P.C. BOARD CONNECTOR ASSEMBLY.		
				3 PLACES	± ---	± ---	CHECKED BY JDENNEHY	DATE 2005/07/07	MOLEX INCORPORATED		
				2 PLACES	± ---	± ---	APPROVED BY JDENNEHY	DATE 2005/07/07			
				1 PLACE	± ---	± ---	MATERIAL NO.	DOCUMENT NO.			
				ANGULAR ± 2 °		SEE SHEET 2		SDA-90147			SHEET NO. 1 OF 2
				DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS				SIZE A3	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		

	10	9	8	7	6	5	4	3	2	1	
F	PART NO'S - STRAIGHT PINS		NO.OF CKTS	DIM." A"	DIM." B" (±0.00) ±.002	QTY. PER TUBE	PLATING VERSION A				
	STANDARD	CUSTOMER SPECIFIC					PRE-PLATED HOT DIP TIN 1.0 TO 2.5 um (.000040" TO .000100").				
	90147-1X02		2	(2.54) .100	(5.08) .200	105	PLATING VERSION E				
	03		3	(5.08) .200	(7.62) .300	72	1.27 TO 1.78 um (.000050" TO .000070") NICKEL				
	04		4	(7.62) .300	(10.16) .400	52	OVERALL, 0.38 TO 0.64 um (.000015" TO .000025")				
	05	90147-9105	5	(10.16) .400	(12.70) .500	44	GOLD ON CONTACT AREA (OVER NICKEL).				
	06		6	(12.70) .500	(15.24) .600	36	3 TO 5 um (.000120" TO .000200") TIN				
	07		7	(15.24) .600	(17.78) .700	30	ON SOLDER TAILS (OVER NICKEL).				
	08		8	(17.78) .700	(20.32) .800	26	PLATING VERSION F.				
	09		9	(20.32) .800	(22.86) .900	22	1.27 TO 1.78 um (.000050" TO .000070") NICKEL				
	10		10	(22.86) .900	(25.40) 1.000	22	OVERALL, 0.76 TO 1.0 um (.000030" TO .000040")				
	11		11	(25.40) 1.000	(27.94) 1.100	20	GOLD ON CONTACT AREA (OVER NICKEL).				
	12		12	(27.94) 1.100	(30.48) 1.200	18	3 TO 5 um (.000120" TO .000200") TIN				
	13		13	(30.48) 1.200	(33.02) 1.300	16	ON SOLDER TAILS (OVER NICKEL).				
	14		14	(33.02) 1.300	(35.56) 1.400	14	PLATING VERSION N.				
	15		15	(35.56) 1.400	(38.10) 1.500	14	1.27 TO 1.78 um (.000050" TO .000070") NICKEL				
	16		16	(38.10) 1.500	(40.64) 1.600	13	OVERALL, 0.76 TO 2.6 um (.000030" TO .000100")				
	17		17	(40.64) 1.600	(43.18) 1.700	13	GOLD ON CONTACT AREA (OVER NICKEL).				
	18		18	(43.18) 1.700	(45.72) 1.800	12	4 um (.000120") MINIMUM TIN				
	19		19	(45.72) 1.800	(48.26) 1.900	12	ON SOLDER TAILS (OVER NICKEL).				
	20		20	(48.26) 1.900	(50.80) 2.000	11	PLATING CODE.				
	21		21	(50.80) 2.000	(53.34) 2.100	11	1 = VERSION A.				
	22		22	(53.34) 2.100	(55.88) 2.200	10	2 = VERSION E.				
	23		23	(55.88) 2.200	(58.42) 2.300	9	3 = VERSION F.				
	24		24	(58.42) 2.300	(60.96) 2.400	9	4 = VERSION N.				
	25		25	(60.96) 2.400	(63.50) 2.500	8	SEE CHART.				
	26		26	(63.50) 2.500	(66.04) 2.600	8					
	27		27	(66.04) 2.600	(68.58) 2.700	8					
	28		28	(68.58) 2.700	(71.12) 2.800	7					
	29		29	(71.12) 2.800	(73.66) 2.900	7					
	30		30	(73.66) 2.900	(76.20) 3.000	7					
	31		31	(76.20) 3.000	(78.74) 3.100	7					
	90147-1X 32		32	(78.74) 3.100	(81.28) 3.200	6					
B											
A	STANDARD PRODUCTS										
	REMOVE KINK OPT EC NO: E2007-0787 DRAWN: WASZKI LEWICZ 2007/04/25 CHKD: JONOR ARTY 2007/04/25 APPR: JDENNEHY 2007/04/27 AA										
QUALITY SYMBOLS ▽=0 ▽=0											
GENERAL TOLERANCES (UNLESS SPECIFIED) mm INCH 4 PLACES ± --- ± --- 3 PLACES ± --- ± --- 2 PLACES ± --- ± --- 1 PLACE ± --- ± --- ANGULAR ± 2 ° DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS											
DIMENSION STYLE MM/IN SCALE 5:1 DESIGN UNITS METRIC THIRD ANGLE PROJECTION DRAWN BY DB DATE 1986/12/28 CHECKED BY JDENNEHY DATE 2005/07/07 APPROVED BY JDENNEHY DATE 2005/07/07 MATERIAL NO. SEE CHART DOCUMENT NO. SDA-90147 SHEET NO. 2 OF 2 THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION											
C-GRID III SINGLE ROW VERTICAL P.C. BOARD CONNECTOR MOLEX INCORPORATED											

STANDARD PRODUCTS

REMOVE KINK OPT
EC NO: E2007-0787
DRWN:DMASZK/EMI C7 2007/04/25
CHKD:DMOR/ARTY 2007/04/25
APPR: DENNEHY 2007/04/27

QUALITY
SYMBOLS
▽=0
▽=0

GENERAL TOLERANCES
(UNLESS SPECIFIED)

	mm	INCH
4 PLACES	± ---	± ---
3 PLACES	± ---	± ---
2 PLACES	± ---	± ---
1 PLACE	± ---	± ---

ANGULAR ± 2 °

DRAFT WHERE APPLICABLE
MUST REMAIN
WITHIN DIMENSIONS

DIMENSION STYLE
MM/IN

DRAWN BY DATE
DB 1986/12/28

CHECKED BY DATE
JDENNEHY 2005/07/07

APPROVED BY DATE
JDENNEHY 2005/07/07

MATERIAL NO.

SIZE
A3

SCALE
5:1

DESIGN UNITS
METRIC

THIRD ANGLE
PROJECTION

TITLE
C-GRID III SINGLE ROW
VERTICAL P.C. BOARD
CONNECTOR

MOLEX MOLEX INCORPORATED

DOCUMENT NO.
SDA-90147

SHEET NO.
2 OF 2

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX
INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION