Reducing bridge - RB UT 35-10 - 3032168

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Reducing bridge, pitch: 13.2 mm, number of positions: 2, color: red

Key Commercial Data

Packing unit	10 pc
Minimum order quantity	10 pc
GTIN	4 055626 130934
GTIN	4055626130934

Technical data

Technical data

Color	red
Material	Copper
Number of positions	2
Pitch	13.2 mm
Ambient temperature (operation)	125 °C
Flammability rating according to UL 94	V0
Maximum load current	57 A (The current values for the jumpers can deviate when used in different modular terminal blocks. The precise values can be found in the accessories data for the respective modular terminal blocks.)

Standards and Regulations

Flammability rating according to UL 94	V0

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Reducing bridge - RB UT 35-10 - 3032168

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approval details

EAC	EAC	RU C-DE.A*30.B.01742

Phoenix Contact 2019 © - all rights reserved
http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
http://www.phoenixcontact.com