

HWS300-5/HD



<b>Sales Region</b>	Worldwide
<b>Series</b>	HWS/HD
<b>Status</b>	Production
<b>Feature</b>	
<b>Option</b>	Harsh environment
<b>Option Lineup</b>	<a href="#">Please refer to here.</a>
<b>Recommended EMC Filter</b>	<a href="#">Please refer to here.</a>
<b>Accessories</b>	<a href="#">Please refer to the catalog</a>



**Electrical Characteristics**

Input Voltage Range[AC]	85 to 265V
Input Voltage Range[DC]	120 to 330V
Efficiency	82% Typ.
Rated Output Voltage[DC]	5V
Output Voltage Range[DC]	4 to 6V
Maximum Output Current	60A
Maximum Output Power	300W

**Cases Shape & Size**

Case'□ shape	Unit
Width(W)	61mm Nom.
Height(H)	82mm Nom.
Depth(D)	165mm Nom.
Weight	1000g Typ.

**Other**

Operating Temp. Range	-10 to 71°C
Cooling	Blower fan cooling
Safety Standard(Certified)	UL60950-1
	CSA C22.2 No.60950-1
	EN60950-1
Safety Standard(Conformed)	EN50178
	Den-an

**Remarks** This page only shows representative characteristics. Please refer to the technical data for detailed specifications and conditions.

! Images are for reference only and show exemplary products.  
! This PDF document was created based on the data listed on the TDK Corporation website.  
! All specifications are subject to change without notice.