



NOTES:

1. FOR USE WITH BOEING BMS13-65 OF AND ADAMS RUSSELL FC14Z CABLES.
2. FOR CABLING INSTRUCTIONS SEE 3-546-1.
3. FOR CRIMPING USE DIE KTH-2232.
4. MARK PACKAGE: KINGS 1525-4-9 (DATE CODE)
5. CONTACT P/N 1-7588-2MA9 TO BE SUPPLIED UNASSEMBLED.
6. MATERIALS:
 GASKET: SIL. RUBBER, A-A-59588
 INSULATOR: TEFLON, ASTM D1710
 SPRING: STAINLESS STEEL WIRE
 OUTER CONTACT: BER. COPPER, ASTM B196
 ALL OTHER PARTS: BRASS, ASTM B16
7. FINISHES:
 CENTER CONTACT: .000050 MIN GOLD PLATE, PER ASTM B488 OVER
 .000050 MIN. NICKEL PER AMS-QQ-N-290 (RoHS)
 ALL OTHER METAL PARTS: .000050 MIN NICKEL PER AMS-QQ-N-290
 OVER .000050 MIN COPPER PER ASTM B734 (RoHS)
8. ELECTRICAL CHARACTERISTICS:
 NOMINAL IMPEDANCE: 50~W
 FREQUENCY RANGE: DC TO 10 GHz
 VOLTAGE RATING: 500 VOLTS RMS
8. WEIGHT: 6.2 GRAMS

1525-4-9

REVISIONS

ISSUE	CHANGES
0	ER 36635 KH 10/18/95
1	CN 37018 B VLS 06/18/96
2	CN 37115 E VLS 09/04/96
D	ER 6515 BAM 02/19/08
E	REVISED PER DMF304 & ER041236 KPL 04/05/12

CUSTOMER
SALES
DRAWING

THIS DRAWING, THE DESIGNS AND IDEAS EMBODIED IN THE DEVICE TO WHICH IT RELATES, AND THE METHOD OF PRODUCING THE DEVICE, ARE THE PROPERTY OF WINCHESTER ELECTRONICS CORPORATION AND SHALL NOT BE EMPLOYED, COPIED, OR DISCLOSED TO ANYONE, IN ANY MANNER WITHOUT THE CONSENT OF WINCHESTER ELECTRONICS CORPORATION.

SCALE	4:1		
APPROX SURFACE AREA			
WAS:	E-19021		
CAGE CODE:	91836		
REF:	BOEING		
PL, TPS			
DRAWN	VLS	DATE	08/17/95
DESIGN	VLS	DATE	08/17/95
APPR.	VLS	DATE	08/17/95



1525-4-9