Shanghai Lunsure Electronic
Technology Co.,LTD
Tel:0086-21-37185008
Fax:0086-21-57152769


AM251 THRU AM256

PRESS FIT AUTOMOTIVE RECTIFIER(MOTOROLA)

VOLTAGE RANGE
100 TO 600 VOLTS
CURRENT 25AMPS

Features

- Low leakage
- Low forward voltage drop
- High current capability
- High forward surge current capability



Dimensions in inches and millimeters

Mechanical Data

- Case: Copper case
- Technology: cell with vcauum soldered
- Polarity: As marked of case bottom
- Lead: Plated lead, solderable per MIL-STD-202E method 208C
- Mounting: Press fit
- Weigth: 9.0 grams

Maximum Ratings and Electrical Charactristics

Rating at 25°C ambient temperature unless otherwise specified
Single phase, half wave, 60Hz, resistive or inductive load
For capacitive load derate current by 20%

Parameters	Symbols	AM251	AM252	AM253	AM254	AM256	Units
Maximum repetitive peak reverse voltage	V_{RRM}	100	200	300	400	600	Volts
Maximum RM S voltage	V_{RMS}	70	140	210	280	420	Volts
Maximum DC blocking voltage	V_{DC}	100	200	300	400	600	Volts
Maximum Average rectified forward current at T_C=110°C	I_o	25					Amps
Peak forward surge current 8.3mS single half sine-wave superimposed on rated load (JE DEC Method)	I_{FSM}	400					Amps
Rating for fusing(t<8.3ms)	I^2t	664					A^2S
Maximum instantaneous forward voltage drop at 100A	V_F	1.08					Volts
Maximum DC reverse current T_A=25°C at rated DC blocking voltage T_A=150°C	I_R	5.0 450					uA
Typical thermal resistance	$R_{\theta JC}$	0.8					°C/W
Operating and storage temperature	T_J,T_{STG}	-65 to +175					°C

Notes: 1.Enough heatsink must be considered in application.

AM251 THRU AM256

Ratings and Characteristic Curves

FIG.1–TYPICAL FORWARD CURRENT DERATING CURVE




FIG.2–MAXIMUM NON–REPETITIVE PEAK FORWARD SURGE CURRENT




FIG.3–TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG.4– FORWARD POWER DISSIPATION

