
AB34S THRU AB320S

SINGLE PHASE GLASS PASSIVATED BRIDGE RECTIFIERS

Voltage Range - 40 to 200 Volts Current - 3.0 Ampere

ABS



Dimensions in inches and (millimeters)

FEATURES

- Ideal for printed circuit board
- Reliable low cost construction utilizing molded plastic technique
- High temperature soldering guaranteed: 260℃/10 seconds at 5 lbs., (2.3kg) tension
- Small size, simple installation
- High surge current capability

MECHANICAL DATA

Case: Molded plastic body
Terminals: Plated leads solderable per MIL-STD-750, Method 2026
Polarity: Polarity symbols marked on case
Mounting Position: Any

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25℃ ambient temperature unless otherwise specified.
Single phase half-wave 60Hz,resistive or inductive load, for capacitive load derate current by 20%.

MDD Catalog Number	SYMBOLS	AB34S	AB36S	AB38S	AB310S	AB320S	UNITS
Maximum repetitive peak reverse voltage	V_{RRM}	40	60	80	100	200	VOLTS
Maximum RMS voltage	V_{RMS}	28	42	56	70	140	VOLTS
Maximum DC blocking voltage	V_{DC}	40	60	80	100	200	VOLTS
Maximum average forward rectified current	$I_{F(AV)}$	3.0					Amps
Peak forward surge current, 8.3ms single half sine-wave superimposed on rated load (JEDEC Method)	I_{FSM}	80		70			Amps
Maximum instantaneous forward voltage drop per leg at 3A	V_F	0.55	0.70	0.85		0.95	Volts
Maximum DC reverse current T_A=25℃ at rated DC blocking voltage T_A=100℃	I_R	0.5 10	0.3 5				mA mA
Typical junction capacitance	C_j	250	160				pF
Typical thermal resistance	$R\theta_{JA}$	60					℃/W
Operating temperature range	T_J	-55 to +125					℃
storage temperature range	T_{STG}	-55 to +150					℃

NOTE:1.Measured at 1MHz and applied reverse voltage of 4 V D.C.

2.Mounted on glass epoxy P C board with 4 X (5X5mm) copper pad.

www.microdiode.com

Download from alldatasheet.com

RATINGS AND CHARACTERISTIC CURVES AB34S THRU AB320S

Fig.1 Forward Current Derating Curve




Fig.2 Typical Reverse Characteristics




Fig.3 Typical Forward Characteristic




Fig.4 Typical Junction Capacitance





Fig.5 Maximum Non-Repetitive Peak Forward Surage Current



www.microdiode.com

Download from alldatasheet.com