



General

Provided equipment	CD with software Documentation CD Installation guide Network management card Rack mounting hardware Rack mounting brackets Rack mounting support rails USB cable Warranty card
--------------------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Physical

Cable length	3.05 m
Number of rack unit	2U
Colour	Black
Depth	63.5 cm
Height	8.5 cm
Net weight	31.3 kg
Width	43.2 cm

Input

Network frequency	40...70 Hz auto-sensing
Plug standard	NEMA L6-20P
Input voltage limits	100...275 V adjustable (half load) 160...275 V
Inputvolt_other	240 V
Input voltage	208 V

Output

Rated power in W	2700 W
Maximum configurable power in W	2700 W
Harmonic distortion	Less than 2 %
Output frequency	50/60 Hz +/- 3 Hz sync to mains
Outputvolt_other	240 V
Crest factor	3 : 1
UPS type	Double conversion online
Wave type	Sine wave
Nb of power socket outlets	2 NEMA L6-20R 1 NEMA L6-30R
Bypass type	Internal bypass (automatic and manual)
Output voltage	208 V

Conformance

Product certifications	ENERGY STAR V2.0 (USA)
Standards	CSA C22.2 No 107.3-05 FCC part 15 class A OSHDP UL 1778

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...10000 ft
Ambient air temperature for storage	-15...45 °C
Storage altitude	0.00...15240.00 m
Acoustic level	55 dBA
Heat dissipation	773 Btu/h
IP degree of protection	IP20

Battery

Battery type	Lead-acid battery
Number of battery filled slots	1
Battery recharge time	3 h
Number of battery replacement quantity	1
Additional information	Configurable for 208 or 240 nominal output voltage
Liquid value	0
Battery voltage	96 V

Communication

Free slots	0
Preinstalled device	Network management card 2 with environmental monitoring
Control panel	Multifunction LCD status and control console
Alarm	Audible and visible alarms prioritized by severity
Emergency power off	Yes

Surge

Surge energy rate	340 J
-------------------	-------

Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Optimized Energy Efficiency	Energy efficient product

Contractual warranty

Warranty	3 years repair or replace (excluding battery) and 2 years for battery
----------	-----------------------------------------------------------------------