


Switching Diode



Features

- Epoxy meets UL-94 V-0 flammability rating
- Moisure Sensitivity Level 1
- High Conductance
- Surface mount package ideally Suited for Automatic Insertion

Mechanical Data

- **Package:** SOT-23
Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant, halogen-free
- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Marking:** KA2

■Maximum Rating, ($T_a=25^{\circ}\text{C}$ Unless otherwise specified)

Item	Symbol	Unit	Value
Reverse Voltage	V_R	V	100
Forward Continuous Current, Per Leg	I_F	mA	150
Non-Repetitive Peak Forward Surge Current@ $t=1\text{s}$,	I_{FSM}	A	1
Power Dissipation	P_D	mW	350
Operation Junction Temperature	T_J	$^{\circ}\text{C}$	-55 to +150
Storage Temperature	T_{STG}	$^{\circ}\text{C}$	-55 to +150

■Ordering Information (Example)

PREFERED P/N	PACKING CODE	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
MMBD4148	F2	Approximate 0.008	3000	30000	120000	7" reel





MMBD4148


■ Electrical Characteristics ($T_a=25^\circ\text{C}$ Unless otherwise specified, Per Leg)

Item	Symbol	Unit	Conditions	Value
Reverse Voltage	V_R	V	$I_R=100\mu\text{A}$	100
Maximum Instantaneous Forward Voltage	V_F	V	$I_{FM}=10\text{mA}$, $T_J=25^\circ\text{C}$	0.855
			$I_{FM}=100\text{mA}$, $T_J=25^\circ\text{C}$	1.2
Maximum DC Reverse Current	I_R	nA	$V_R=20\text{V}$	25
		μA	$V_R=75\text{V}$	5
Typical Junction Capacitance	C_J	pF	$f=1.0\text{MHz}$, $V_R=0\text{V}$	4
Reverse Recovery Time	T_{rr}	ns	$I_F=10\text{mA}$, $V_R=6\text{V}$, $R_L=500\Omega$, $I_{rr}=1\text{mA}$	4

■ Typical Characteristics (Per Leg)






Leakage current versus junction temperature






MMBD4148

■SOT-23 Package Outline Dimensions



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	0.900	1.150	0.035	0.045
A1	0.000	0.100	0.000	0.004
A2	0.900	1.050	0.035	0.041
b	0.300	0.500	0.012	0.020
c	0.100	0.200	0.004	0.008
D	2.800	3.000	0.110	0.118
E	1.200	1.400	0.047	0.055
E1	2.250	2.550	0.089	0.100
e	0.950TYP		0.037TYP	
e1	1.800	2.000	0.071	0.079
L	0.550REF		0.022REF	
L1	0.300	0.500	0.012	0.020
θ	0°	8°	0°	8°

■SOT-23Suggested Pad Layout





Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.