



N-Channel Enhancement Mode Mosfet



Feature:

- Low Crss
- Low Gate Charge
- Fast Switching
- Improved ESD Capability
- Improved dv/dt Capability
- 100% Avalanche Energy Test



Mechanical Data:

- **Package: MOS**
Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant
- **Terminal: Tin plated leads.**
Solderable per J-STD-002 and JESD22-B102
- **Polarity:** As marked on body

■ Ordering Information

P/N	PACKAGE	PACKING CODE	UNIT WEIGHT(g)	MINIIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
YJ12N65CI	ITO-220AB	B1	Approximate 1.7	50	1000	5000	TUBE
YJ12N65CZ	TO-220AB	B1	Approximate 1.6	50	1000	5000	TUBE
YJ12N65CM	TO-263	B1	Approximate 2.0	50	1000	5000	TUBE


■ Maximum Ratings (T_a=25°C Unless otherwise specified)

Parameter	Symbol	Value	Unit
Drain-Source Voltage	V _{DSS}	650	V
Continues Drain Current	I _D	T _c =25°C	11.5*
		T _c =100°C	6.8*
Plused Drain Current (note 1)	I _{DM}	46	A
Gate-to-Source Voltage	V _{GS}	±30	V
Single Pulsed Avalanche Energy (note 2)	E _{AS}	590	mJ
Avalanche Current (note 1)	I _{AR}	11	A
Repetitive Avalanche Energy (note 1)	E _{AR}	20	mJ
Peak Diode Recovery (note 3)	dv/dt	4.5	V/ns
Power Dissipation	P _D T _c =25°C	TO-220AB	240
		ITO-220AB	50
Power Dissipation Derating Factor	P _{D(DF)} Above 25°C	TO-220AB	2.0
		ITO-220AB	0.4
Operating and Storage Temperature Range	T _J , T _{STG}	150, -55~+150	°C
Maximum Temperature for Soldering	T _L	300	°C

■ Electrical Characteristics (T_a=25°C Unless otherwise specified)

Off-Characteristics						
Parameter	Symbol	Tests Conditions	Min	Type	Max	Unit
Drain-Source Breakdown Voltage	BV _{DSS}	I _D =250μA, V _{GS} =0V	650	-	-	V
Breakdown Voltage Temperature Coefficient	ΔBV _{DSS} /ΔT _J	I _D =250μA, referenced to 25°C	-	0.7	-	V/°C
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} =650V, V _{GS} =0V, T _c =25°C	-	-	1	μA
		V _{DS} =520V, T _c =125°C	-	-	10	
Gate-body leakage current, forward	I _{GSSF}	V _{DS} =0V, V _{GS} =30V	-	-	100	nA
Gate-body leakage current, reverse	I _{GSSR}	V _{DS} =0V, V _{GS} =-30V	-	-	-100	nA



On-Characteristics						
Parameter	Symbol	Tests Conditions	Min	Type	Max	Unit
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS} = V_{GS}, I_D = 250\mu A$	2.0	-	4.0	V
Static Drain-Source On-Resistance	$R_{DS(ON)}$	$V_{GS} = 10V, I_D = 6.0A$	-	0.65	0.75	Ω
Forward Transconductance	g_{fs}	$V_{DS} = 40V, I_D = 6.0A$ (note4)	-	10	-	S

Dynamic Characteristics						
Parameter	Symbol	Tests Conditions	Min	Type	Max	Unit
Input capacitance	C_{iss}	$V_{DS} = 25V, V_{GS} = 0V, f = 1.0MHz$	-	1887	2507	pF
Output capacitance	C_{oss}		-	188	243	pF
Reverse transfer capacitance	C_{rss}		-	18	28	pF

Switching Characteristics						
Parameter	Symbol	Tests Conditions	Min	Type	Max	Unit
Turn-On delay time	$t_d(on)$	$V_{DD} = 325V, I_D = 12A, R_G = 25\Omega$ (note 4, 5)	-	78	102	ns
Turn-On rise time	t_r		-	133	175	ns
Turn-Off delay time	$t_d(off)$		-	233	310	ns
Turn-Off Fall time	t_f		-	105	180	ns
Total Gate Charge	Q_g	$V_{DS} = 520V, I_D = 12A, V_{GS} = 10V$ (note 4, 5)	-	55	70	nC
Gate-Source charge	Q_{gs}		-	10	-	nC
Gate-Drain charge	Q_{gd}		-	25	-	nC

Drain-Source Diode Characteristics and Maximum Ratings						
Parameter	Symbol	Tests Conditions	Min	Type	Max	Unit
Maximum Continuous Drain-Source Diode Forward Current		I_S	-	-	12	A
Maximum Pulsed Drain-Source Diode Forward Current		I_{SM}	-	-	48	A
Drain-Source Diode Forward Voltage	V_{SD}	$V_{GS} = 0V, I_S = 12A$	-	-	1.4	V
Reverse recovery time	t_{rr}	$V_{GS} = 0V, I_S = 12A$ $di_F/dt = 100A/\mu s$ (note 4)	-	450	-	ns
Reverse recovery charge	Q_{rr}		-	4.9	-	μC

■ Thermal Characteristics (T_a=25°C Unless otherwise specified)

Parameter	Symbol		Max	Unit
Thermal Resistance, Junction to Case	Rth(j-c)	TO-220AB	0.52	°C/W
		ITO-220AB	2.5	
Thermal Resistance, Junction to Ambient	Rth(j-A)	TO-220AB	62.5	°C/W
		ITO-220AB	62.5	

* Drain current limited by maximum junction temperature

Notes:

- 1: Pulse width limited by maximum junction temperature
- 2: L=11.5mH, I_{AS}=12A, V_{DD}=50V, R_G=25Ω, Starting T_J=25°C
- 3: I_{SD} ≤ 12A, di/dt ≤ 300A/μs, V_{DD} ≤ BV_{DSS}, Starting T_J=25°C
- 4: Pulse Test: Pulse Width ≤ 300μs, Duty Cycle ≤ 2%
- 5: Essentially independent of operating temperature

■ Characteristics (Typical)




Fig. 1 On-State Characteristics




Fig. 2 Transfer Characteristics




Fig. 3 Breakdown Voltage Variation vs Temperature




Fig. 4 On-Resistance Variation vs Temperature




Fig. 5 Capacitance Characteristics




Fig. 6 Gate Charge Characteristics




Fig. 7 Maximum Safe Operating Area




Fig. 8 Maximum Drain Current vs Case Temperature




Fig. 9 Transient Thermal Response Curve(TO-220AB)





Fig. 10 Transient Thermal Response Curve(ITO-220AB)


■ Outline Dimensions

ITO-220AB



Symbol	Min	Max	Symbol	Min	Max
A	9.96	10.36	D	2.54	
A1	7.00		D1	1.15	1.35
A2	3.08	3.28	D2	0.70	0.90
A3	9.25	9.65	D3	0.28	0.48
B1	15.70	16.10	E	2.34	2.74
B2	4.50	4.90	E1	0.70	
B3	6.20	6.80	E2	1.0×45°	
C	3.20	3.40	E3	0.36	0.65
C1	15.20	16.00	E4	2.55	2.95
C2	9.75	10.15	a(度)	30°	

TO-220AB



Symbol	Min	Normal	Max	Symbol	Min	Normal	Max
A	4.4	4.5	4.6	e		2.54	
A1	1.27	1.3	1.33	e1		5.08	
A2	2.3	2.4	2.5	H1	6.3	6.5	6.7
b	0.7	/	0.9	L	13.0	13.38	13.5
b1	1.25		1.42	L1	/	/	3.5
c	0.45	0.5	0.6	L2		4.6	
D	15.3	15.7	16.1	ΦP	3.55	3.6	3.65
D1	9.1	9.2	9.3	Q	2.73	/	2.87
E	9.7	9.9	10.2	$\theta 1$ ($^{\circ}$)	1	3	5



Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website <http://www.21yangjie.com>, or consult your nearest Yangjie's sales office for further assistance.