



SCF series

Programmable Time Delay Relay

- 4 user-programmable timing modes
- 0.1 sec. to 10 hr. programmable timing range
- Parameters set with recessed dials
- Narrow width saves panel space
- 10A DPDT output relay
- Socket can be DIN-rail or back panel mounted

File E15631(relay) and E140494 (socket)

File LR29186 (relay) and LR29513M7 (socket)

Users should thoroughly review the technical data before selecting a product part number. It is recommended that user also seek out the pertinent approvals files of the agencies/laboratories and review them to ensure the product meets the requirements for a given application.

Timing Modes

Modes are user selectable via screwdriver adjustment of recessed 4-position selector dial.
Modes offered are: On-Delay, Off-Delay, Interval and Latching Interval.

Timing Specifications

Timing Ranges: 0.1 to 3 / 0.33 to 10 / 1 to 30 / 4 to 120 sec.; 0.33 to 10 / 1 to 30 / 2 to 60 min.; 0.33 to 10 hr.

Timing Range Selection: Screwdriver select via recessed 8-position selector dial.

Timing Adjustment: External knob potentiometer adjustment with reference calibrations.

Accuracy: Repeat Accuracy: $\pm 1\% \pm 0.01$ sec.
Overall Accuracy: $\pm 3\% \pm 0.01$ sec.

Reset Time: 30 ms.

Relay Operate Time: On-Delay and Interval mode: 55 ms.

Relay Release Time: Off-Delay, Interval and Latching Interval: 40 ms.

Contact Data @ 25°C

Arrangements: 2 Form C (DPDT).

Rating: 10A @ 28VDC or 120VAC, resistive; 1/3 HP @ 120/240VAC; 345VA.


Expected Mechanical Life: 10 million operations.

Expected Electrical Life: 500,000 operations, min., at rated resistive load.


Initial Dielectric Strength

Between Terminals and Case: 1,000VAC plus twice the nominal voltage for one minute.

Outline Dimensions



Wiring Diagram (Bottom View)



Input Data @ 25°C

Voltage: See Ordering Information section for details.

Power Requirement: 2W, max.

Transient Protection: Non-repetitive transients of the following magnitudes will not cause spurious operation of affect function and accuracy.

Operating Voltage	<0.1 ms	<1 ms
12VDC	1,000V	240V*
24VAC/VDC	1,000V	240V*
48 VAC/VDC	1,000V	480V*
120 VAC, 125VDC	3,000V	2,500V*
240VAC/VDC	3,000V	2,500V*

* Minimum source impedance of 100 ohm.

Environmental Data

Temperature Range: Storage: -40°C to +85°C.

Operating: -30°C to +65°C.

Mechanical Data

Mounting/Termination: 11-pin octal-type plug for use with mating socket.

Mount relay in horizontal position (pins horizontal, knob down, LEDs up).

Status Indication: Power On LED and Output Contacts LED.

Weight: Relay: 3.5 oz. (156g) approx.; Socket: 1.7 oz. (48.3g) approx.

Ordering Information

SCF	RX	90	2	A	A
Series SCF	Operating Mode	Output Rating			
Plug-In Programmable Timer	90 = Multiple Modes On-Delay Off-Delay Interval Latching Interval	A = 10 Amp B = 5 Amp			
Mounting	Output	Operating Voltage (+10%, -15%)			
RX = Without Socket RF = With Socket	2 = DPDT Relay	A = 120VAC, 50/60 Hz. / 125VDC B = 240VAC, 50/60 Hz. § E = 24VAC, 50/60 Hz. / 24VDC F = 48VAC, 50/60 Hz. / 24VDC Q = 12VDC			
		§ Voltage Option B is only available with 5 Amp output option.			

Authorized distributors are likely to stock the following:

None at present.