
This document was generated on 05/21/2010

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0014563099
Status: Active
Overview: cgrid__sl_products
Description: 2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 28, 0.38µm (15µ") Gold (Au), 9 Circuits



Series image - Reference only

Documents:

- 3D Model
- Drawing (PDF)
- Product Specification PS-70400 (PDF)
- RoHS Certificate of Compliance (PDF)

Agency Certification

CSA	LR19980
UL	E29179

General

Product Family	Ribbon Cable / Wire Trap Connectors
Series	70400
Comments	Terminals Preloaded
Component Type	Housing
Glow-Wire Compliant	No
Overview	cgrid__sl_products
Product Name	SL™

Physical

Circuits (Loaded)	9
Color - Resin	Black
Durability (mating cycles max)	50
Entry Angle	Vertical
Flammability	94V-0
Lock to Mating Part	None
Material - Metal	Phosphor Bronze
Material - Plating Mating	Gold
Material - Plating Termination	Tin
Material - Resin	Polyester Alloy
Number of Rows	1
PCB Retention	None
Packaging Type	Tube
Pitch - Mating Interface (in)	0.100 In
Pitch - Mating Interface (mm)	2.54 mm
Plating min: Mating (µin)	15
Plating min: Mating (µm)	0.375
Plating min: Termination (µin)	75
Plating min: Termination (µm)	1.875
Polarized to Mating Part	Yes
Stackable	Yes
Surface Mount Compatible (SMC)	N/A
Temperature Range - Operating	-40°C to +105°C
Termination Interface: Style	IDT or Pierce
Wire Insulation Diameter	1.35mm (.053") max.
Wire Size AWG	28
Wire/Cable Type	Discrete Wire, Ribbon Cable

Electrical

Current - Maximum per Contact	3A
Voltage - Maximum	250V

Material Info

EU RoHS
ELV and RoHS Compliant
REACH SVHC
Not Reviewed
Halogen-Free Status
Not Reviewed

China RoHS

Need more information on product environmental compliance?

Email productcompliance@molex.com
For a multiple part number RoHS Certificate of Compliance, click here

Please visit the Contact Us section for any non-product compliance questions.

Search Parts in this Series
70400Series

Mates With
70004 Interim Clip (Single Row), 70013 Interim Clip (Dual Row)

Use With
7307 Tinned 28AWG, 7767 Topcoat 28AWG, 24241 Tinned 26AWG, 8996 Topcoat 26AWG, 24226 Tinned 24AWG, 8997 Topcoat 24AWG, 24369 High Flex 26AWG, 24389 High Flex 24AWG

Application Tooling | **FAQ**

Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.

Global

Description	Product #
Hawk Semi-Automatice Discrete	0011201337


Old Part Number	70400-0953


Reference - Drawing Numbers

Product Specification	PS-70400
Sales Drawing	SDA-70400-0946-0969

Wire Terminator for SL - Rebuilt US*	
Hawk™ Ribbon Cable Terminator for SL without Break-off	0623003000
Hawk™ Semi-Automatic Discrete Wire Terminator for SL - Rebuilt CE Approved*	0623004900
Hawk™ Flat Flex Cable Terminator for SL with Break-off	0623005200
Hawk™ Ribbon Cable Terminator with for SL Break-off	0623005300
IDT Discrete Handtool Module for SL™	0621000700
Hawk™ Semi-Automatic Discrete Wire Terminator for SL	0623003100

OPTION D






NOTES:

1) TO BE USED WITH (28) AWG. STRANDED WIRE WITH (1.35)/.053 DIA. MAX. INSULATION.
2) SEE CHART FOR CIRCUIT SIZES.
3) STANDARD PACKAGING PER PK-70873-0001. OPTIONAL PACKAGING MAY BE AVAILABLE, REQUEST DWG. PK-70400
4) PARTS STACKABLE END TO END ON (2.54)/.100 CENTERS.
5) REFER TO PRODUCT SPECIFICATION: PS-70400.
6) SEE DWG. SDA-70400-**** (SHT. 5) FOR OPTIONAL HOUSING DETAILS.
7) 4 CIRCUIT SHOWN. 3 - 25 CKT'S. HAVE (2) RIBS.
8) TO MATE WITH MOLEX PART NO'S.: 70004-****, 70013-****
9) 2 CIRCUIT ASSEMBLIES SUPPLIED AS GROUPED PAIRS.



SECTION C-C



CKT. SIZE	A	B	EDP. NO.	ENG. NO.
2	(2.54) .100	(5.05) .199	14-56-3029	A-70400-0946
3	(5.08) .200	(7.59) .299	14-56-3039	A-70400-0947
4	(7.62) .300	(10.13) .399	14-56-3049	A-70400-0948
5	(10.16) .400	(12.67) .499	14-56-3059	A-70400-0949
6	(12.70) .500	(15.21) .599	14-56-3069	A-70400-0950
7	(15.24) .600	(17.75) .699	14-56-3079	A-70400-0951
8	(17.78) .700	(20.29) .799	14-56-3089	A-70400-0952
9	(20.32) .800	(22.83) .899	14-56-3099	A-70400-0953
10	(22.86) .900	(25.37) .999	14-56-3109	A-70400-0954
11	(25.54) 1.000	(27.91) 1.099	14-56-3119	A-70400-0955
12	(27.94) 1.100	(30.45) 1.199	14-56-3129	A-70400-0956
13	(30.48) 1.200	(32.99) 1.299	14-56-3139	A-70400-0957
14	(33.02) 1.300	(35.53) 1.399	14-56-3149	A-70400-0958
15	(35.56) 1.400	(38.07) 1.499	14-56-3159	A-70400-0959
16	(38.01) 1.500	(40.61) 1.599	14-56-3169	A-70400-0960
17	(40.64) 1.600	(43.15) 1.699	14-56-3179	A-70400-0961
18	(43.18) 1.700	(45.69) 1.799	14-56-3189	A-70400-0962
19	(45.72) 1.800	(48.23) 1.899	14-56-3199	A-70400-0963
20	(48.26) 1.900	(50.77) 1.999	14-56-3209	A-70400-0964
21	(50.80) 2.000	(53.31) 2.099	14-56-3219	A-70400-0965
22	(53.34) 2.100	(55.85) 2.199	14-56-3229	A-70400-0966
23	(55.88) 2.200	(58.39) 2.299	14-56-3239	A-70400-0967
24	(58.42) 2.300	(60.93) 2.399	14-56-3249	A-70400-0968
25	(60.96) 2.400	(63.47) 2.499	14-56-3259	A-70400-0969

I.D. SLOT CODE TO WIRE GAUGE CHART	
I.D. SLOT CODE	WIRE GAUGE
C	28 AWG.

PLATING CODE (STRIPE ON CARRIER STRIP)	
PLATING	COLOR
15 GOLD	YELLOW

15 GOLD - .000015 MIN. GOLD IN SELECT AREA WITH .000075 MIN. TIN IN SELECT AREA OVER .000050 MIN. NICKEL OVER-ALL.

*THE PRIMARY SHIPPING CARTON WILL BE LABELED "COMPLIANT TO RoHS DIRECTIVE 2002/95/EC AND ELV ANNEX II OF DIRECTIVE 2000/53/EC". CARTONS WITHOUT THIS LABEL MAY CONTAIN PRODUCT WITH LEAD.

LTR.	REVISIONS	LTR.	REVISIONS
		D	REVISED PER ECR NO. U82110 10-17-88 AAB
E	LEAD FREE UCP2004-1769 RWHITE 04/03/17	C	REVISE PER ECR #U80110 2/3/88 MJM
D1	ADD CARRIER CHAMF ECN #UDT1998-0280 05/20/98 LMCGRATH	B	REDRAWN ON CAD ECR# 8842 5/8/86 W.Z.

DIMENSIONS SHOWN (METRIC) INCH
UNLESS OTHERWISE SPECIFIED TOLERANCES: ANGULAR ± 1/2°

	INCH	METRIC
3 PLACE	± .010	---
2 PLACE	± .014	± 0.25
1 PLACE	---	± 0.35

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

DRWG. BY WAZ | CHK'D. BY WAZ | APP'D. BY | SCALE 4 : 1

MFG. | SH. | REV.

▽ = ▼ = REVISE ONLY ON CAD SYSTEM

TITLE: ASSEMBLY, SL CONNECTOR (SINGLE ROW- (2.54)/.100 GRID)

molex MOLEX INCORPORATED LISLE,ILL. 60532 U.S.A.

SHEET NO. | DATE 10/10/84

PART NO. SEE CHART | DRWG. NO. SDA-70400-0946-0969

FILE NAME S70400DX6

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INC. AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.

DIV. DA | SIZE C

70400