Silicon Power Diode

PSM/PSMR 40L $I_{F(AV)}$ = 40 A
PSM/PSMR 40K V_{RRM} = 100 - 1600 V


Preliminary Data Sheet

V_{RRM} max.repetitive peak voltage (V)	$V_{R(RMS)}$ max.RMS reverse voltage (V)	V_R max. DC blocking voltage (V)	recommended RMS working voltage (V)	Type without terminal lead	Type with terminal lead
100	70	100	40	PSM/PSMR 40/01L	PSM/PSMR 40/01K
200	140	200	80	PSM/PSMR 40/02L	PSM/PSMR 40/02K
400	280	400	160	PSM/PSMR 40/04L	PSM/PSMR 40/04K
600	420	600	240	PSM/PSMR 40/06L	PSM/PSMR 40/06K
800	560	800	320	PSM/PSMR 40/08L	PSM/PSMR 40/08K
1000	700	1000	400	PSM/PSMR 40/10L	PSM/PSMR 40/10K
1200	840	1200	480	PSM/PSMR 40/12L	PSM/PSMR 40/12K
1400	980	1400	560	PSM/PSMR 40/14L	PSM/PSMR 40/14K
1600	1120	1600	640	PSM/PSMR 40/16L	PSM/PSMR 40/16K


Symbol	Conditions		Maximum Ratings	
$I_{F(AV)}$	T_C = 140°C		40	A
I_{FSM}	T_{VJ} = 45°C t = 10 ms		500	A
I_{FRM}	max. peak cycle repetitive surge current		200	A
I^2t	max. I^2t rating (non-rep.) for 5 to 10 ms		1200	A^2s
$I_{R(AV)}$	max. average reverse leakage current at V_{RRM}; T_C = 25°C		200	µA
V_{FM}	max. peak forward voltage drop @ rated 1F(AV)		1.3	V
R_{thJC}	max. thermal resistance junction to case		0.65	K/W
T_{VJ}	operating junction temperature		-65... + 150	°C
T_{VJM}	max. virtual junction temperature		150	°C
T_{stg}	storage temperature		-65... + 200	°C
M_d	mounting torque	min.	0.4	mkg
	(non-lubricated threads)	max.	0.6	mkg
Weight	PSM/PSMR 40L	typ.	13.5	g
Weight	PSM/PSMR 40K	typ.	30	g

DO - 5

PSM/PSMR 40L



PSM/PSMR 40K



Features

- All Diffused Series
- Available in Normal & Reverse Polarity
- Industrial Grade
- Available in Avalanche Characteristic

POWERSEM GmbH, Walpersdorfer Str. 53
D - 91126 Schwabach
Phone: 09122 - 9764 - 0 FAX: 09122 - 9764 - 20

© 2005 POWERSEM reserves the right to change limits, test conditions and dimensions