

塑封超快速整流二极管


反向电压 50 --- 600 V

正向电流 1.0 A

Plastic Super Fast Recover Rectifier

Reverse Voltage 50 to 600V

Forward Current 1.0A

**特征 Features**

- 反向漏电流低 Low reverse leakage
- 正向浪涌承受能力较强 High forward surge capability
- 高温焊接保证 High temperature soldering guaranteed:
260°C/10 秒, 0.375" (9.5mm)引线长度。
260°C/10 seconds, 0.375" (9.5mm) lead length,
- 引线可承受5 磅 (2.3kg) 拉力。 5 lbs. (2.3kg) tension
- 引线和管体皆符合RoHS标准 。
Lead and body according with RoHS standard

机械数据 Mechanical Data

- 端子: 镀锡轴向引线 Terminals: Plated axial leads
- 极性: 色环端为负极 Polarity: Color band denotes cathode end
- 安装位置: 任意 Mounting Position: Any

极限值和温度特性 TA = 25°C 除非另有规定。

Maximum Ratings & Thermal Characteristics Ratings at 25°C ambient temperature unless otherwise specified.

	符号 Symbols	ER100	ER101	ER101A	ER102	ER103	ER104	ER106	单位 Unit
最大可重复峰值反向电压 Maximum repetitive peak reverse voltage	V _{RRM}	50	100	150	200	300	400	600	V
最大均方根电压 Maximum RMS voltage	V _{RMS}	35	70	105	140	210	280	420	V
最大直流阻断电压 Maximum DC blocking voltage	V _{DC}	50	100	150	200	300	400	600	V
最大正向平均整流电流 Maximum average forward rectified current	I _{F(AV)}					1.0			A
峰值正向浪涌电流 8. 3ms单一正弦半波 Peak forward surge current 8.3 ms single half sine-wave	I _{FSM}					30			A
典型热阻 Typical thermal resistance	R _{θJA}				65				°C/W
工作结温和存储温度 Operating junction and storage temperature range	T _j , T _{TG}				-55 --- +150				°C

电特性 TA = 25°C 除非另有规定。

Electrical Characteristics Ratings at 25°C ambient temperature unless otherwise specified.

	符号 Symbols	ER100	ER101	ER101A	ER102	ER103	ER104	ER106	单位 Unit
最大正向电压 Maximum forward voltage	I _F = 1.0A	V _F		0.95		1.3		1.7	V
最大反向电流 Maximum reverse current	TA= 25°C TA=100°C	I _R			5.0 100				μA
最大反向恢复时间 MAX. Reverse Recovery Time	I _F =0.5A I _R =1.0A I _{RR} =0.25A	t _{rr}			35				nS
典型结电容 Type junction capacitance	V _R = 4.0V, f = 1MHz	C _j			17				pF

特性曲线 Characteristic Curves

