



Price* : 18,828.00 USD



Main

Product or component type	Automatic switch
Range of product	PowerPact P
Current sensor rating range	1200 A
Line Rated Current	1200 A
Breaking capacity	100 kA 240 V AC 65 kA 480 V AC 25 kA 600 V AC
Trip unit technology	Magnetic
Accessory / separate part type	Shunt trip 24 V AC Auxiliary switch 3 NO + 3 NC

Complementary

Product certifications	UL Listed CSA IEC
[Ue] rated operational voltage	600 V AC
Module type	P-Frame
Mounting location	Busbar
Mounting mode	Unit mount
Poles description	3P
Breaking capacity code	J
Electrical connection	Busbar connection line Busbar connection load
Maximum Height	16.16 in (410.46 mm)
Maximum Depth	8.05 in (204.47 mm)
Maximum Width	8.27 in (210.06 mm)
Tightening torque	442.54 lbf.in (50 N.m) 0.15...0.37 in ² (95...240 mm ²) AWG 3/0...500 kcmil)

* Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Ordering and shipping details

Category	01215-PG,H,J,K,L,N UNIT MT BREAKERS
Discount Schedule	DE2
GTIN	00785901755098
Package weight(Lbs)	32.00 lb(US) (14.515 kg)
Returnability	No
Country of origin	US

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: DINP and DIDP which is known to the State of California to cause Carcinogen and Reproductive harm. For more information go to www.p65warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------