FR301 THRU FR307


Reverse Voltage - 50 to 1000 Volts Forward Current - 3.0 Ampere

FAST RECOVERY RECTIFIERS

Features

DO-201AD RoHS COMPLIANT

- The plastic package carries Underwriters Laboratory Flammability Classification 94V-0 Idea for
- printed circuit board
- Fast switching for high efficiency
- Low reverse leakage
- High forward surge current capability
- High temperature soldering guaranteed: 250℃/ 10 seconds at terminals



Dimensions in inches and (millimeters)

Mechanical Data

Case : JEDEC DO-201AD Molded plastic body
Terminals : Solder plated, solderable per MIL-STD-750,Method 2026
Polarity : Polarity symbol marking on body
Mounting Position : Any
Weight : 0.04 ounce, 1.10 grams

Maximum Ratings And Electrical Characteristics

Ratings at 25°C ambient temperature unlss otherwise specified.

Single phase half-wave 60Hz,resistive or inductive load,for capacitive load current derate by 20%.

Parameter	SYMBOLS	FR301	FR302	FR303	FR304	FR305	FR306	FR307	UNITS
Marking Code		MDD FR301	MDD FR302	MDD FR303	MDD FR304	MDD FR305	MDD FR306	MDD FR307	
Maximum repetitive peak reverse voltage	V_{RMM}	50	100	200	400	600	800	1000	V
Maximum RMS voltage	V_{RMS}	35	70	140	280	420	560	700	V
Maximum DC blocking voltage	V_{DC}	50	100	200	400	600	800	1000	V
Maximum average forward rectified current at T_A=75℃	$I_{(AV)}$	3.0							A
Peak forward surge current 8.3ms single half sine-wave superimposed onrated load (JEDEC Method)	I_{FSM}	200							A
Maximum instantaneous forward voltage at 3.0A	V_F	1.30							V
Maximum DC reverse current T_A=25℃ at rated DC blocking voltage T_A=100℃	I_R	5.0 100.0							μA
Maximum reverse recovery time (NOTE 1)	trr	150				250	500		ns
Typical junction capacitance (NOTE 2)	C_J	60.0							pF
Typical thermal resistance (NOTE 3)	$R_{\theta JA}$	20.0							℃/W
Operating junction and storage temperature range	T_J,T_{STG}	-65 to +150							℃

Note:1.Reverse recovery condition I_F=0.5A,I_R=1.0A,Irr=0.25A
2.Measured at 1MHz and applied reverse voltage of 4.0V D.C.
3.Thermal resistance from junction to ambient at 0.375"(9.5mm)lead length,P.C.B. mounted

Download from alldatasheet.com

Ratings And Characteristic Curves

FIG. 1- FORWARD CURRENT DERATING CURVE




FIG. 2-MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




FIG. 3-TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG. 4-TYPICAL REVERSE CHARACTERISTICS




FIG. 5-TYPICAL JUNCTION CAPACITANCE





FIG. 6-TYPICAL TRANSIENT THERMAL IMPEDANCE



The curve above is for reference only.

Download from alldatasheet.com