

1. Mechanical Dimensions:



2. Schematic:



3. Electrical Specifications: @25°C

Isolation: 1500 Vrms (PRI to SEC)

TX Turns Ratio: 1:1.36CT (PRI:SEC)

RCV Turns Ratio: 1:2CT (PRI:SEC)

PRI OCL: 1.20mH Minimum @100KHz, 50mV

Cw/w: 35pF Maximum @100KHz, 50mV (PRI/SEC)

PRI LL: 0.8uH Maximum @100KHz 50mV
(SEC Shorted)

Q: 5 Min @10KHz, 50mV

Notes:

1. Solderability: Leads shall meet MIL-STD-202G, Method 208H for solderability.
2. Flammability: UL94V-0
3. ASTM oxygen index: > 28%
4. Insulation System: Class F 155°C. UL file E151556
5. Operating Temperature Range: All listed parameters are to be within tolerance from -40°C to +85°C
6. Storage Temperature Range: -55°C to +125°C
7. Aqueous wash compatible
8. SMD Lead Coplanarity: ±0.004"(0.102mm)
9. Electrical and mechanical specifications 100% tested
10. RoHS Compliant Component
11. Recommended IR Reflow peak temp of 235°C Max.

DOC. REV: B/1

PROPRIETARY Document is the property of XFMRS Group & is not allowed to be duplicated without authorization.

XFMRS Inc www.XFMRS.com	Title: T1/E1/CEPT QUAD PORT		
UNLESS OTHERWISE SPECIFIED TOLERANCES: .xxx ±0.010 Dimensions in Inch	P/N: XF0013Q1B		REV. B
	DWN.	Yuan	Sep-22-14
	CHK.	YK Liao	Sep-22-14
SHEET 1 OF 1	APP.	DDC	Sep-22-14