

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:

0687850006

Status:

Active

Overview:

displayport

Description:

Mini DisplayPort*(Plug)-to-Mini DisplayPort*(Plug) Cable Assembly, 2.0m (6.56'), Lead-free



Series
image - Reference only

Documents:

[Drawing \(PDF\)](#)

[Product Specification PS-68785-0004 \(PDF\)](#)

[RoHS Certificate of Compliance \(PDF\)](#)

General	
Product Family	Cable Assemblies
Series	68785
Connector to Connector	Mini DisplayPort* Both Ends
Overview	displayport
Product Name	DisplayPort*, Mini DisplayPort*
Physical	
Cable Length	2.0m (6.56')
Circuits (Loaded)	20
Color - Resin	Black
Gender	Male-Male
Lock to Mating Part	Yes
Material - Metal	Copper Alloy
Material - Plating Mating	Gold
Material - Resin	High Temperature Thermoplastic
Packaging Type	Carton
Pitch - Mating Interface (in)	0.024 In
Pitch - Mating Interface (mm)	0.60 mm
Single Ended	No
Waterproof / Dustproof	No
Wire Insulation Diameter	N/A
Wire/Cable Type	Round
Electrical	
Current - Maximum per Contact	.5A
Impedance	100 ohms
Shield Type	Full Shield
Shielded	Yes
Voltage - Maximum	40V AC

Material Info

Reference - Drawing Numbers

Product Specification

PS-68785-0004

Sales Drawing

SD-68785-0004

Mini DisplayPort* and DisplayPort* are trademarks or registered trademarks of VESA

EU RoHS

ELV and RoHS

Compliant

REACH SVHC

Not Reviewed

Halogen-Free

Status

Not Reviewed

China RoHS

Need more information on product environmental compliance?

Email productcompliance@molex.com

For a multiple part number RoHS Certificate of Compliance, [click here](#)

Please visit the [Contact Us](#) section for any non-product compliance questions.

Search Parts in this Series

68785Series

Mates With

105081 Mini DisplayPort* Receptacles

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

REVISIONS				CHANGER
ECN NO	DATE	REVISION	DESCRIPTION	
	SEP 07,09	A	INITIAL RELEASE	JOE XIE




TABLE-1:

687850006	2000±40
687850005	1500±30
687850004	1000±20
PART NO.	LENGTH

EC NO: DG2010-0085 DRWN:YX/E CHKD:CLU0 APPR:CLU0 A	DESCRIPTION REV	QUALITY SYMBOLS <div>▽=0</div> <div>◻=0</div>	GENERAL TOLERANCES (UNLESS SPECIFIED)			DIMENSION STYLE MM ONLY		SCALE ---	DESIGN UNITS METRIC	<div>THIRD ANGLE PROJECTION</div>	MINIDP PLUG TO MINIDP PLUG CABLE ASSY	
				mm	INCH	DRAWN BY		DATE	TITLE			
			4 PLACES	± ---	± ---	CHECKED BY		DATE				
			3 PLACES	± ---	± ---	APPROVED BY		DATE	<div>molex</div> MOLEX INCORPORATED			
			2 PLACES	± 0.25	± ---	MATERIAL NO.		DOCUMENT NO.			SHEET NO.	
			1 PLACE	± 0.5	± ---	SEE TABLE-1		SD-68785-0004				1 OF 2
			DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS			SIZE A 4	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION					

7

6

5

4


3

2

1

WIRING DIAGRAM

MINI DP PLUG SOURCE SIDE	FUNCTION	MINI DP PLUG SINK SIDE
PIN 01	GROUND	PIN 08
PIN 03	ML0+	PIN 12
PIN 05	ML0-	PIN 10
PIN 07	GROUND	PIN 13
PIN 09	ML1+	PIN 17
PIN 11	ML1-	PIN 15
PIN 13	GROUND	PIN 07
PIN 15	ML2+	PIN 11
PIN 17	ML2-	PIN 09
PIN 19	GROUND	PIN 19
PIN 02	HOT PLUG DETECT	PIN 02
PIN 04	CONFIG 1	PIN 04
PIN 06	CONFIG 2	PIN 06
PIN 08	GROUND	PIN 01
PIN 10	ML3+	PIN 05
PIN 12	ML3-	PIN 03
PIN 14	GROUND	PIN 14
PIN 16	AUX+	PIN 16
PIN 18	AUX-	PIN 18
PIN 20	NO CONNECTION	PIN 20
SHELL	GROUND	SHELL



NOTES:

1. MATERIALS:

OVERMOLD: PVC, COLOR BLACK, UL94-V0.

CABLE: PVC JACKET, BLACK, UL94-VW-1.

HOUSING: HIGH TEMPERATURE THERMOPLASTIC.

TERMINAL: COPPER ALLOY, GOLD PLATING, NICKEL UNDERPLATE.

SHELL: COPPER ALLOY, NICKEL PLATING.

2. ELECTRICAL PROPERTY:

3.1 APPLIED VOLTAGE RATING: 40V AC (RMS).

3.2 CURRENT RATING: 0.5A.

3.3 DIELECTRIC WITHSTAND: 300V.

3.4 INSULATION RESISTANCE: 100M OHM (UNMATING),

10M OHM (MATING).

3. OPERATION TEMPERATURE: -20°C TO +80°C.

4. THE PRODUCT COMPLIANT TO MOLEX ES-40000-5016.

ITEM	DESCRIPTION	MATERIAL	USAGE
E	MINI DP CABLE	---	---
D	BOTTOM SHELL FOR MINI DP PLUG	COPPER ALLOY	2 PCS
C	TOP SHELL FOR MINI DP PLUG	COPPER ALLOY	2 PCS
B	SHIELD SHELL FOR MINI DP PLUG	COPPER ALLOY	2 PCS
A	SUB-ASSEMBLY FOR MINI DP PLUG	---	2 PCS

EC NO: DG2010-0085		2009/11/02		2009/11/03		2009/11/03		DESCRIPTION		QUALITY SYMBOLS		GENERAL TOLERANCES (UNLESS SPECIFIED)			DIMENSION STYLE MM ONLY			SCALE ---		DESIGN UNITS METRIC		THIRD ANGLE PROJECTION						
A		DRWN:Y0XIE		CHKD:CLU0		APPR:CLU0				 =0  =0		mm			INCH			DRAWN BY		DATE		MINIDP PLUG TO MINIDP PLUG CABLE ASSY						
												4 PLACES			± ---			± ---			CHECKED BY					DATE		
												3 PLACES			± ---			± ---			APPROVED BY		DATE		MOLEX INCORPORATED			
												2 PLACES			± 0.25			± ---										
												1 PLACE			± 0.5			± ---										
ANGULAR ± 3 °			DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS			MATERIAL NO. SEE TABLE-1			DOCUMENT NO. SD-68785-0004			SHEET NO. 2 OF 2																
REV												SIZE A 4			THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION													

6

5

4

3

2

1