



Circular Plug Connectors IP68
Circular Plug Connectors AC 169 kompakt
AC 169 REBU/ 5 M20



Panel Mount Socket, 5 pole, Voltage Rating: 450 V, Current Rating: 17.5 A, Cross-Section: 1.5 mm²

Order Info

Reference Number (ref. no.)	728815D3
Applications	Lighting, Installation
PU	200
EAN	4028012133130

Type

Type	Panel Mount Socket
Number of poles	5 pole
Clamping Units per Pole	1
Colour	black
Cross-Section	1.5 mm ²
Connection Type	Screw
PE Function	yes
Protection Against Incorrect Plugging	yes

Technical Data

Voltage Rating	450 V
Current Rating	17.5 A
Insulating Material	PA 6.6
Contact Material	Brass
Core Cross-Section min.	0.5 mm ²
Core Cross-Section max.	1.5 mm ²
Impulse Voltage Rating	4.0 kV
Flammability Rating	V-2
max. Ambient Temperature Operation	85 °C
IP Code	IP68
Type of Conductor Solid	yes
Type of Conductor Flexible	yes
Type of Conductor Stranded	yes
Stripping Length	6.0 mm
Dismantling Length	20.0 mm
Assembly Contact Screw	0.5x3.0 / ⚡ 0.2 Nm

Housing Hole Diameter	M20
------------------------------	-----

Accessories

AC 169 RVKB M20	729184
------------------------	--------

AC 169 RWZ/ 5	749965
----------------------	--------
