FAIRCHILD SEMICONDUCTOR TM

September 2000

IGBT

FM2G100US60

Molding Type Module

General Description


Fairchild IGBT Power Module provides low conduction and switching losses as well as short circuit ruggedness. It's designed for the applications such as motor control, UPS and general inverters where short-circuit ruggedness is required.

Features

- Short Circuit rated 10us @ T_C = 100°C, V_{GE} = 15V
- High Speed Switching
- Low Saturation Voltage : $V_{CE(sat)}$ = 2.2 V @ I_C = 100A
- High Input Impedance
- Fast & Soft Anti-Parallel FWD



Package Code : 7PM-AA



Internal Circuit Diagram

Application

- AC & DC Motor Controls
- General Purpose Inverters
- Robotics
- Servo Controls
- UPS

Absolute Maximum Ratings

T_C = 25°C unless otherwise noted

Symbol	Description		FM2G100US60	Units
V_{CES}	Collector-Emitter Voltage		600	V
V_{GES}	Gate-Emitter Voltage		± 20	V
I_C	Collector Current	@ T_C = 25°C	100	A
$I_{CM\ (1)}$	Pulsed Collector Current		200	A
I_F	Diode Continuous Forward Current	@ T_C = 100°C	100	A
I_{FM}	Diode Maximum Forward Current		200	A
T_{SC}	Short Circuit Withstand Time	@ T_C = 100°C	10	us
P_D	Maximum Power Dissipation	@ T_C = 25°C	400	W
T_J	Operating Junction Temperature		-40 to +150	°C
T_{stg}	Storage Temperature Range		-40 to +125	°C
V_{iso}	Isolation Voltage	@ AC 1minute	2500	V
Mounting Torque	Power Terminals Screw : M5		2.0	N.m
	Mounting Screw : M5		2.0	N.m

Notes :
(1) Repetitive rating : Pulse width limited by max. junction temperature

©2000 Fairchild Semiconductor International

Electrical Characteristics of IGBT T_C = 25°C unless otherwise noted

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
Off Characteristics						
BV_{CES}	Collector-Emitter Breakdown Voltage	V_{GE} = 0V, I_C = 250uA	600	--	--	V
$\Delta B_{VCES}/\Delta T_J$	Temperature Coeff. of Breakdown Voltage	V_{GE} = 0V, I_C = 1mA	--	0.6	--	V/°C
I_{CES}	Collector Cut-Off Current	V_{CE} = V_{CES}, V_{GE} = 0V	--	--	250	uA
I_{GES}	G-E Leakage Current	V_{GE} = V_{GES}, V_{CE} = 0V	--	--	± 100	nA
On Characteristics						
$V_{GE(th)}$	G-E Threshold Voltage	I_C = 0V, I_C=100mA	5.0	--	8.5	V
$V_{CE(sat)}$	Collector to Emitter Saturation Voltage	I_C = 100A, V_{GE} = 15V	--	2.2	2.8	V
Dynamic Characteristics						
C_{ies}	Input Capacitance	V_{CE} = 30V, V_{GE} = 0V, f = 1MHz	--	10840	--	pF
C_{oes}	Output Capacitance		--	963	--	pF
C_{res}	Reverse Transfer Capacitance		--	228	--	pF
Switching Characteristics						
$t_{d(on)}$	Turn-On Delay Time	V_{CC} = 300 V, I_C = 100A, R_G = 2.4Ω, V_{GE} = 15V Inductive Load, T_C = 25°C	--	25	--	ns
t_r	Rise Time		--	70	--	ns
$t_{d(off)}$	Turn-Off Delay Time		--	120	150	ns
t_f	Fall Time		--	86	200	ns
E_{on}	Turn-On Switching Loss		--	4.0	--	mJ
E_{off}	Turn-Off Switching Loss		--	2.6	--	mJ
E_{ts}	Total Switching Loss		--	6.6	--	mJ
$t_{d(on)}$	Turn-On Delay Time	V_{CC} = 300 V, I_C = 100A, R_G = 2.4Ω, V_{GE} = 15V Inductive Load, T_C = 125°C	--	34	--	ns
t_r	Rise Time		--	96	--	ns
$t_{d(off)}$	Turn-Off Delay Time		--	175	--	ns
t_f	Fall Time		--	160	--	ns
E_{on}	Turn-On Switching Loss		--	5.0	--	mJ
E_{off}	Turn-Off Switching Loss		--	4.9	--	mJ
E_{ts}	Total Switching Loss		--	9.9	--	mJ
T_{sc}	Short Circuit Withstand Time	V_{CC} = 300 V, V_{GE} = 15V @ T_C = 100°C	10	--	--	us
Q_g	Total Gate Charge	V_{CE} = 300 V, I_C = 100A, V_{GE} = 15V	--	425	500	nC
Q_{ge}	Gate-Emitter Charge		--	80	--	nC
Q_{gc}	Gate-Collector Charge		--	200	--	nC

©2000 Fairchild Semiconductor International

Electrical Characteristics of DIODE T_C = 25°C unless otherwise noted

Symbol	Parameter	Test Conditions		Min.	Typ.	Max.	Units
V_{FM}	Diode Forward Voltage	I_F = 100A	T_C = 25°C	--	1.9	2.8	V
			T_C = 100°C	--	1.8	--	
t_{rr}	Diode Reverse Recovery Time	I_F = 100A di / dt = 200 A/us	T_C = 25°C	--	90	130	ns
			T_C = 100°C	--	130	--	
I_{rr}	Diode Peak Reverse Recovery Current		T_C = 25°C	--	9	12	A
			T_C = 100°C	--	12	--	
Q_{rr}	Diode Reverse Recovery Charge		T_C = 25°C	--	405	790	nC
			T_C = 100°C	--	780	--	

Thermal Characteristics

Symbol	Parameter	Typ.	Max.	Units
$R_{\theta JC}$	Junction-to-Case (IGBT Part, per 1/2 Module)	--	0.31	°C/W
$R_{\theta JC}$	Junction-to-Case (DIODE Part, per 1/2 Module)	--	0.7	°C/W
$R_{\theta CS}$	Case-to-Sink (Conductive grease applied)	0.05	--	°C/W
Weight	Weight of Module	--	190	g

©2000 Fairchild Semiconductor International




Fig 1. Typical Output Characteristics




Fig 2. Typical Saturation Voltage Characteristics




Fig 3. Saturation Voltage vs. Case Temperature at Variant Current Level




Fig 4. Load Current vs. Frequency




Fig 5. Saturation Voltage vs. V_{GE}




Fig 6. Saturation Voltage vs. V_{GE}

©2000 Fairchild Semiconductor International




Fig 7. Capacitance Characteristics




Fig 8. Turn-On Characteristics vs. Gate Resistance




Fig 9. Turn-Off Characteristics vs. Gate Resistance




Fig 10. Switching Loss vs. Gate Resistance




Fig 11. Turn-On Characteristics vs. Collector Current




Fig 12. Turn-Off Characteristics vs. Collector Current

©2000 Fairchild Semiconductor International




Fig 13. Switching Loss vs. Collector Current




Fig 14. Gate Charge Characteristics




Fig 15. SOA Characteristics




Fig 16. Turn-Off SOA Characteristics




Fig 17. RBSOA Characteristics




Fig 18. Transient Thermal Impedance

©2000 Fairchild Semiconductor International




Fig 19. Forward Characteristics





Fig 20. Reverse Recovery Characteristics

©2000 Fairchild Semiconductor International

Package Dimension

7PM-AA (FS PKG CODE BD)



Dimensions in Millimeters

©2000 Fairchild Semiconductor International

TRADEMARKS

The following are registered and unregistered trademarks Fairchild Semiconductor owns or is authorized to use and is not intended to be an exhaustive list of all such trademarks.

ACEx™
Bottomless™
CoolFET™
CROSSVOLT™
DOME™
E^2CMOS™
EnSigna™
FACT™
FACT Quiet Series™
FAST®
FASTr™
GlobalOptoisolator™
GTO™
HiSeC™
ISOPLANAR™
MICROWIRE™
OPTOLOGIC™
OPTOPLANAR™
POP™
PowerTrench®
QFET™
QS™
QT Optoelectronics™
Quiet Series™
SuperSOT™-3
SuperSOT™-6
SuperSOT™-8
SyncFET™
TinyLogic™
UHC™
VCX™

DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR INTERNATIONAL.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.

2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

PRODUCT STATUS DEFINITIONS

Definition of Terms

Datasheet Identification	Product Status	Definition
Advance Information	Formative or In Design	This datasheet contains the design specifications for product development. Specifications may change in any manner without notice.
Preliminary	First Production	This datasheet contains preliminary data, and supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.
No Identification Needed	Full Production	This datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.
Obsolete	Not In Production	This datasheet contains specifications on a product that has been discontinued by Fairchild semiconductor. The datasheet is printed for reference information only.

©2000 Fairchild Semiconductor International