

1 550 nm OPTICAL FIBER COMMUNICATIONS

EA MODULATOR INTEGRATED MQW-DFB LASER DIODE MODULE

FOR 2.5 Gb/s ULTRALONG-REACH APPLICATIONS

DESCRIPTION


The NDL7910P is an EA modulator integrated 1 550 nm DFB-LD for 2.5 Gb/s. The newly developed bandgap energy controlled Selective MOVPE technology is utilized as fabrication method. It is designed for 2.5 Gb/s ultralong-reach applications.

FEATURES


- Integrated electroabsorption modulator
- Low modulation voltage
- Wavelength selectable for ITU-T standards
- 14-pin butterfly package

PACKAGE DIMENSIONS

in millimeters



TOP VIEW



PIN CONNECTIONS

Pin No.	Function	Pin No.	Function
1	Thermistor	8	GND
2	Thermistor	9	GND
3	LD DC Bias	10	NC
4	PD Anode	11	GND
5	PD Cathode	12	Signal Input (MOD), 50 Ω RF Input
6	Cooler Anode	13	GND
7	Cooler Cathode	14	GND

The information in this document is subject to change without notice.

ORDERING INFORMATION

Part Number	Available Connector
NDL7910P	Without Connector
NDL7910PC	With FC-PC Connector

ABSOLUTE MAXIMUM RATINGS (T_c = 25 °C, unless otherwise specified)

Parameter	Symbol	Ratings	Unit
Optical Output Power from Fiber	P _f	10	mW
Forward Current of LD	I _{FLD}	150	mA
Reverse Voltage of LD	V _{RLD}	2.0	V
Forward Voltage of Modulator	V _{Fm}	1	V
Reverse Voltage of Modulator	V _{Rm}	5	V
Forward Current of PD	I _{FPD}	1	mA
Reverse Voltage of PD	V _{RPD}	10	V
Cooler Current	I _c	1.5	A
Cooler Voltage	V _c	2.5	V
Operating Case Temperature	T _c	−20 to +70	°C
Storage Temperature	T _{stg}	−40 to +85	°C
Lead Soldering Temperature (10 s)	T _{slid}	260	°C

ELECTRO-OPTICAL CHARACTERISTICS

(T_{LD} = 25 °C, T_c = −20 to +70 °C, unless otherwise specified)

Parameter	Symbol	Conditions	MIN.	TYP.	MAX.	Unit
Operating Current	I _{op}		50		100	mA
Modulation Center Voltage	V _{Rmc}		0.5		1.5	V
Modulation Voltage	V _{Rmpp}		2		3	V
Forward Voltage of LD	V _{FLD}	I _{FLD} = I _{op}			1.8	V
Threshold Current	I _{th}			7	20	mA
Optical Output Power from Fiber	P _f	V _{Rm} = 0 V, I _{FLD} = I _{op}	0.5			mW
Peak Emission Wavelength	λ _p	I _{FLD} = I _{op} , V _{Rm} = 0 V	1 545		1 560	nm
Spectral Line Width	Δν	I _{FLD} = I _{op} , −20 dB, Under modulation ^{*1}		4		GHz
Side Mode Suppression Ratio	SMSR	I _{FLD} = I _{op} , V _{Rm} = 0 V	30			dB
Extinction Ratio	ER	I _{FLD} = I _{op} , Under modulation ^{*1}	10			dB
Cut-off Frequency	f _c	I _{FLD} = I _{op} , V _{Rm} = 1/2 V _{Rmpp} , −3 dB, 50 Ω	3.2			GHz
Rise Time	t _r	I _{FLD} = I _{op} , 20-80 %, Under modulation ^{*1}			125	ps
Fall Time	t _f	I _{FLD} = I _{op} , 80-20 %, Under modulation ^{*1}			125	ps
Isolation	I _s		30			dB


*1 2.48832 Gb/s, PRBS 2²³⁻¹, V_{Rm} = V_{Rmc} ± 1/2 V_{Rmpp}, NEC Test System

ELECTRO-OPTICAL CHARACTERISTICS

(Applicable to Monitor PD: $T_{LD} = 25\text{ }^{\circ}\text{C}$, $T_c = -20\text{ to }+70\text{ }^{\circ}\text{C}$)

Parameter	Symbol	Conditions	MIN.	TYP.	MAX.	Unit
Monitor Current	I_m	$I_{FLD} = I_{op}$, $V_{Rm} = 0\text{ V}$	20		1 000	μA
Dark Current	I_D	$V_{RPD} = 5\text{ V}$			10	nA
Tracking Error	γ^{*1}	$I_m = \text{const.}$			0.5	dB
Monitor Capacitance	C_t	$V_{RPD} = 5\text{ V}$, $f = 1\text{ MHz}$			15	pF

$$*1 \gamma = \left| 10 \log \frac{P_f}{P_{op}} \right|$$




ELECTRO-OPTICAL CHARACTERISTICS

(Applicable to Thermistor and TEC: $T_{LD} = 25\text{ }^{\circ}\text{C}$, $T_c = -20\text{ to }+70\text{ }^{\circ}\text{C}$)


Parameter	Symbol	Conditions	MIN.	TYP.	MAX.	Unit
Thermistor Resistance	R	$T_{LD} = 25\text{ }^{\circ}\text{C}$	9.5	10.0	10.5	$\text{k}\Omega$
B Constant	B		3 300	3 400	3 500	K
Cooler Current	I_c	$\Delta T = 70 - T_{set}$			1.5	A
Cooler Voltage	V_c	$\Delta T = 70 - T_{set}$			2.5	V

TYPICAL CHARACTERISTICS ($T_{LD} = 25\text{ }^{\circ}\text{C}$, unless otherwise specified)

OPTICAL OUTPUT POWER FROM FIBER vs.
FORWARD CURRENT OF LD (CW)



EXTINCTION RATIO vs. MODULATION
VOLTAGE (CW)



Remark The graphs indicate nominal characteristics.

★ DFB-LD FAMILY FOR TELECOM

Part Number	Absolute Maximum Ratings		Typical Characteristics			SDH Application	Package
	T _c (°C)	T _{stg} (°C)	I _{th} (mA)	P _r (mW)	λ _c (nm)		
			TYP.	MIN.	TYP.		
NDL7603P Series	−40 to +85	−40 to +85	15	2	1 310	≤ STM-4 : 622 Mb/s	Coaxial
NDL7620P Series	0 to +70	−40 to +85	45 (MAX.)	2	1 310	≤ STM-16: 2.5 Gb/s	Coaxial
NDL7701P Series	−20 to +85	−40 to +85	15	2	1 550	≤ STM-4 : 622 Mb/s	Coaxial
NDL7705P Series	−40 to +85	−40 to +85	15	2	1 550	≤ STM-4 : 622 Mb/s	Coaxial
NX8562LB	−20 to +65	−40 to +85	20	20	1 550 ^{*1}	CW Light Source for external modulator	BFY
NX8563LB Series	−20 to +65	−40 to +85	20	10	ITU-T ^{*2}	CW Light Source for external modulator	BFY
NDL7910P	−20 to +70	−40 to +85	7	0.5	1 550 ^{*1}	≤ STM-16: 2.5 Gb/s EA modulator integrated DFB-LD	BFY

*1 Wavelength selectable for ITU-T standards upon request.

*2 Wavelength selectable for ITU-T standards.


REFERENCE

Document Name	Document No.
NEC semiconductor device reliability/quality control system	C11159E
Quality grades on NEC semiconductor devices	C11531E
Semiconductor device mounting technology manual	C10535E
Semiconductor selection guide	X10679E


[MEMO]

CAUTION

Within this device there exists GaAs (Gallium Arsenide) material which is a harmful substance if ingested. Please do not under any circumstances break the hermetic seal.



SEMICONDUCTOR LASER



NEC Corporation

NEC Building, 7-1, Shiba 5-chome,
Minato-ku, Tokyo 108-01, Japan

Type number: _____

Manufactured: _____

Serial Number: _____

This product conforms to FDA
regulations as applicable
to standards 21 CFR Chapter 1.
Subchapter J.

The export of this product from Japan is prohibited without governmental license. To export or re-export this product from a country other than Japan may also be prohibited without a license from that country. Please call an NEC sales representative.

No part of this document may be copied or reproduced in any form or by any means without the prior written consent of NEC Corporation. NEC Corporation assumes no responsibility for any errors which may appear in this document.

NEC Corporation does not assume any liability for infringement of patents, copyrights or other intellectual property rights of third parties by or arising from use of a device described herein or any other liability arising from use of such device. No license, either express, implied or otherwise, is granted under any patents, copyrights or other intellectual property rights of NEC Corporation or others.

While NEC Corporation has been making continuous effort to enhance the reliability of its semiconductor devices, the possibility of defects cannot be eliminated entirely. To minimize risks of damage or injury to persons or property arising from a defect in an NEC semiconductor device, customers must incorporate sufficient safety measures in its design, such as redundancy, fire-containment, and anti-failure features.

NEC devices are classified into the following three quality grades:

"Standard", "Special", and "Specific". The Specific quality grade applies only to devices developed based on a customer designated "quality assurance program" for a specific application. The recommended applications of a device depend on its quality grade, as indicated below. Customers must check the quality grade of each device before using it in a particular application.

Standard: Computers, office equipment, communications equipment, test and measurement equipment, audio and visual equipment, home electronic appliances, machine tools, personal electronic equipment and industrial robots

Special: Transportation equipment (automobiles, trains, ships, etc.), traffic control systems, anti-disaster systems, anti-crime systems, safety equipment and medical equipment (not specifically designed for life support)

Specific: Aircrafts, aerospace equipment, submersible repeaters, nuclear reactor control systems, life support systems or medical equipment for life support, etc.

The quality grade of NEC devices is "Standard" unless otherwise specified in NEC's Data Sheets or Data Books. If customers intend to use NEC devices for applications other than those specified for Standard quality grade, they should contact an NEC sales representative in advance.

Anti-radioactive design is not implemented in this product.