

## ZWS75BAF-48



Sales Region	Worldwide	
Series	ZWS-BAF	-
Status	Production	
Feature		
Option		
Option Lineup	Please refer to here.	
Recommended EMC Filter	Please refer to here.	-
Accessories	Please refer to the catalog	

Electri	cal Characteristics
Input Voltage Range[AC]	85 to 265V
Input Voltage Range[DC]	120 to 370V
Efficiency	88% Typ.
Rated Output Voltage[DC]	48V
Output Voltage Range[DC]	39.5 to 52.8V
Maximum Output Current	1.6A
Maximum Output Power	76.8W

Cases Shape & Size		
Case' ] shape	PC board	
Width(W)	50mm Nom.	
Height(H)	33mm Nom.	
Depth(D)	150mm Nom.	
Weight	230g Typ.	

Other		
Operating Temp. Range	-10 to 70°C	
Cooling	Convection cooling	
	UL60950-1	
Safety Standard (Cortified)	CSA C22.2 No.60950-1	
Safety Standard(Certified)	EN60950-1	
	EN50178 (OV II)	
Safety Standard(Conformed)	Den-an	
Demonto	This page only shows representative characteristics. Please refer to the	
Remarks	technical data for detailed specifications and conditions.	

! Images are for reference only and show exemplary products. ! This PDF document was created based on the data listed on the TDK Corporation website.

! All specifications are subject to change without notice.