


<b>Sales Region</b>	Worldwide (except Japan)
<b>Series</b>	ALE
<b>Model</b>	ALE-Rack mount
<b>Status</b>	 Production
<b>Option</b>	Negative polarity
<b>Option Lineup</b>	<a href="#">Please refer to here.</a>
<b>Accessories</b>	<a href="#">Please refer to the catalog</a>



### Electrical Characteristics

Input	3-phase
Input Voltage Range[AC]	180 to 254VAC
Input Frequency Range	47 to 63Hz
Rated Output Voltage[DC]	1000Vdc
Output Voltage Range[DC]	0 to 1000V
Average Capacitor Charging Power	18000J/sec
Peak Capacitor Charging Power	22000J/sec
Charge Current	50A
Continuous DC Current	30A
Continuous DC Power	30kW
Polarity	Negative
Power Factor	0.9
Efficiency	85% Typ.

### Package Type & Size

Package / Mounting	Rack mount
Width(W)	482mm Nom. (18.98in Nom.)
Height(H)	311mm Nom. (12.24in Nom.)
Depth(D)	571mm Nom. (22.48in Nom.)
Weight	100kg Typ. (220.5lbs Typ.)

### Other

Operating Temp. Range	0 to 55°C
Storage Temp. Range	-40 to 70°C
Cooling	Water
Safety Standard(Certified)	
Safety Standard(Conformed)	

Remarks This page only shows representative characteristics. Please refer to the technical data for detailed specifications and conditions.