
LS914

SWITCHING DIODES

VOLTAGE 100 Volts **POWER** 500 mWatts

QUADRO-MELF Unit : inch (mm)



FEATURES

- Fast switching Speed.
- Electrically Identical to Standerd JEDEC
- High Conductance
- Axial lead Package Ideally Suited for Automatic Insertion.
- In compliance with EU RoHS 2002/95/EC directives

MECHANICAL DATA

- Case: Molded GlassQUADRD MELF
- Terminals: Solderable per MIL-STD-750, Method 2026
- Polarity: See Diagram Below
- Approx. Weight: 0.030 grams
- Mounting Position: Any
- Packing information

  T/R - 10K per 13" plastic Reel

  T/R - 2.5K per 7" plastic Reel


MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS (T_J =25°C unless otherwise noted)

PARAMETER	SYMBOL	LS914	UNITS
Reverse Voltage	V_R	75	V
Peak Reverse Voltage	V_{RM}	100	V
RMS Voltage	V_{RMS}	50	V
Maximum Average Forward Current at T_A=25°C And f ≥ 50Hz	$I_{F(AV)}$	75	mA
Surge Forward Current at t < 1s and T_J=25 °C	I_{FSM}	500	mA
Power Dissipation at Tamb= 25 °C	P_{TOT}	500	mW
Maximum Forward Voltage at I_F =10mA	V_F	1.0	V
Maximum Leakage Current at V_R=20V at V_R=75V at V_R=20V ,T_J= 150 °C	I_R	 25 5 50	 nA µA µA
Maximum Capacitance (Note 1)	C_J	4	pF
Maximum Reverse Recovery Time (Note 2)	t_{rr}	4	ns
Typical Thermal Resistance	$R_{\theta JA}$	350	°C / W
Junction Temperature and Storage Temperature Range	T_J,T_s	-65 to +175	°C


NOTE:

1. CJ at V_R=0, f=1MHZ
2. From I_F=10mA to I_R=1mA, V_R=6Volts, R_L=100Ω


LS914




FORWARD VOLTAGE



LEAKAGE CURRENT



TYPICAL CAPATICANCE




POWER DERATING

LS914

MOUNTING PAD LAYOUT

QUADRO-MELF Unit: inch (mm)



ORDER INFORMATION

- Packing information

T/R - 10K per 13" plastic Reel

T/R - 2.5K per 7" plastic Reel

LEGAL STATEMENT

Copyright PanJit International, Inc 2009

The information presented in this document is believed to be accurate and reliable. The specifications and information herein are subject to change without notice. Pan Jit makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose. Pan Jit products are not authorized for use in life support devices or systems. Pan Jit does not convey any license under its patent rights or rights of others.