SBR4045CT
SBR4045CTFP

40A SBR®
Super Barrier Rectifier

NEW PRODUCT

Features

- Low Forward Voltage Drop
- Excellent High Temperature Stability
- Super Barrier Design
- Soft, Fast Switching Capability
- Molded Plastic TO-220AB, and ITO-220AB packages
- **Lead Free Finish, RoHS Compliant (Note 2)**

Mechanical Data

- Case Material: Molded Plastic, UL Flammability Classification Rating 94V-0
- Moisture Sensitivity: Level 1 per J-STD-020C
- Terminals: Matte Tin Finish annealed over Copper leadframe. Solderable per MIL-STD-202, Method 208 e3
- Marking: See Page 3
- Ordering Information: See Page 3

Maximum Ratings @ T_A = 25ºC unless otherwise specified

Single phase, half wave, 60Hz, resistive or inductive load.
For capacitive load, derate current by 20%.

Characteristic	Symbol	Value	Unit
Peak Repetitive Reverse Voltage Working Peak Reverse Voltage DC Blocking Voltage	V_{RRM} V_{RWM} V_{RM}	45	V
RMS Reverse Voltage	$V_{R(RMS)}$	32	V
Average Rectified Output Current @T_C = 110ºC	I_O	40	A
Non-Repetitive Peak Forward Surge Current 8.3ms Single Half Sine-Wave Superimposed on Rated Load	I_{FSM}	280	A
Peak Repetitive Reverse Surge Current (2uS-1Khz)	I_{RRM}	2	A
Maximum Thermal Resistance (per leg) Package = TO-220AB Package = ITO-220AB	$R_{\Theta JC}$	 2 4	°C/W
Operating and Storage Temperature Range	T_J, T_{STG}	-65 to +150	ºC

Electrical Characteristics @ T_A = 25ºC unless otherwise specified

Characteristic	Symbol	Min	Typ	Max	Unit	Test Condition
Reverse Breakdown Voltage (Note 1)	$V_{(BR)R}$	45	-	-	V	I_R = 0.5 mA
Forward Voltage Drop	V_F	-	- 0.47	0.55 0.50	V	I_F = 20A, T_J = 25ºC I_F = 20A, T_J = 125ºC
Leakage Current (Note 1)	I_R	-	-	0.5 100	mA	V_R = 45V, T_J = 25 ºC V_R = 45V, T_J = 125 ºC

Notes:
1. Short duration pulse test used to minimize self-heating effect.
2. RoHS revision 13.2.2003. High temperature solder exemption applied, see *EU Directive Annex Note 7.*

SBR is a registered trademark of Diodes Incorporated.

© Diodes Incorporated

NEW PRODUCT




Figure 1: Current Derating Curve, Per Element




Figure 2: Typical Forward Characteristics, Per Element





Figure 3: Typical Reverse Characteristics, Per Element


Package Outline Drawings

TO-220AB



TO-220AB		
DIM.	MIN.	MAX.
A	4.47	4.67
b	0.71	0.91
b1	1.17	1.37
c	0.31	0.53
D	14.65	15.35
D1	8.50	8.90
E	10.01	10.31
e	2.54 typ	
e1	4.98	5.18
F	1.17	1.37
J1	2.52	2.82
L	13.40	13.80
L1	3.56	3.96
ØP	3.735	3.935
Q	2.59	2.89
All Dimensions in Millimeters		

ITO-220AB






ITO-220AB		
DIM.	MIN.	MAX.
A	4.30	4.70
b	0.50	0.75
b1	1.10	1.35
b2	1.50	1.75
c	0.50	0.75
D	14.80	15.20
E	9.96	10.36
e	2.54 typ	
F	2.80	3.20
J1	2.50	2.90
L	12.80	13.60
L1	1.70	1.90
ØP	3.50 typ	
Q	2.70 typ	
All Dimensions in Millimeters		

© Diodes Incorporated

NEW PRODUCT

Marking, Polarity, Weight & Ordering Information

	SBR4045CT	SBR4045CTFP
Case Style	 TO-220AB	 ITO-220AB
Polarity	Case 	
Marking		
Weight	2.1g	1.9g

Ordering Information	SBR4045CT 50 pieces/tube	SBR4045CTFP 50 pieces/tube
Date Code	YY = Last two digits of year, ex = 06 = 2006 WW = Week (01-52)	
Other Marking Information	A = Foundry Code B = Assembly Code	

IMPORTANT NOTICE

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to any product herein. Diodes Incorporated does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

Diodes Incorporated products are not authorized for use as critical components in life support devices or systems without the expressed written approval of the President of Diodes Incorporated.

© Diodes Incorporated