


Rocker Switches

15 x 10 mm SP Ultra Miniature Rocker Switch

RK8 Series



RK8S1D8D _ _ ON-OFF


TERMINAL



ACTUATOR




ACTUATOR MARKING



PANEL SIZE

PANEL CUT-OUT
Snap-in mounting



X (Panel thickness)	Dimension Y	Dimension Z
0.75 to 1.25 mm	13.6 +0/-0.1 mm	9.20 ±0.1 mm
1.25 to 2.00 mm	13.7 +0/-0.1 mm	9.20 ±0.1 mm
2.00 to 2.50 mm	13.8 +0/-0.1 mm	9.20 ±0.1 mm

How to order:

RK8

1 POLES:
S Single Pole

2 SWITCHING:
1 ON - OFF
2 ON - ON
4 MOM - OFF

3 TERMINAL (See above drawings):
D Solder Tag

4 ACTUATOR (See above drawings):
8 Flat

5 ACTUATOR MARKING:
A See above drawings
B See above drawings
C See above drawings
D See above drawings
E See above drawings
F See above drawings

6 BASE COLOR:
A Black
H Grey
B White

7 ACTUATOR COLOR:
A Black
H Grey
B White
C Red

General Specifications:

FEATURES

- » Single pole mini size rocker switch
- » Appealing outlook
- » Non illuminated

MATERIALS

- » Movable Contact: Silver alloy
- » Stationary Contact: Silver alloy
- » Terminals: Silver plated copper
- » Spring: Piano wire

MECHANICAL

- » Temperature Range: 0°C to +100°C

ELECTRICAL

- » Electrical Life: 10,000 cycles
- » Rating: 6A 125VAC / 3A 250VAC
3A 250VAC
- » Initial Contact Resistance: 20mΩ max.
- » Insulation Resistance: 100MΩ min. at 500VDC