
240 Amp Schottky Rectifier

HS24230



Std. Polarity
Base is cathode
Rev. Polarity
Base is anode

Dim.	Inches		Millimeter		
	Minimum	Maximum	Minimum	Maximum	Notes
A	1.52	1.56	38.86	39.62	
B	.725	.775	18.42	19.69	
C	.605	.625	15.37	15.88	
D	1.182	1.192	30.02	30.28	
E	.745	.755	18.92	19.18	Sq.
F	.152	.160	3.86	4.06	Dia.
G		1/4-20 UNC-2B			
H	.570	.580	14.49	14.73	
J	.156	.160	3.96	4.06	
K	.495	.505	12.57	12.83	Dia.
L	.120	.130	3.05	3.30	

Microsemi Catalog Number	Working Peak Reverse Voltage	Repetitive Peak Reverse Voltage
HS24230*	30V	30V

*Add Suffix R for Reverse Polarity

- Schottky Barrier Rectifier
- Guard Ring Protection
- 240 Amperes/30 Volts
- 150°C Junction Temperature
- Reverse Energy Tested

Electrical Characteristics

Average forward current	$I_{F(AV)}$ 240 Amps	T_C = 84°C, Square wave, $R_{\theta JC}$ = .24°C/W
Maximum surge current	I_{FSM} 3500 Amps	8.3ms, half sine, T_J = 150°C
Maximum repetitive reverse current	$I_{R(OV)}$ 2 Amps	f = 1 KHZ, 25°C
Max peak forward voltage	V_{FM} 0.49 Volts	I_{FM} = 240A: T_J = 125°C*
Max peak forward voltage	V_{FM} 0.55 Volts	I_{FM} = 240A: T_J = 25°C*
Max peak reverse current	I_{RM} 3 Amp	V_{RRM}, T_J = 125°C*
Max peak reverse current	I_{RM} 12mA	V_{RRM}, T_J = 25°C
Typical junction capacitance	C_J 10500pF	V_R = 5.0V, T_C = 25°C

*Pulse test: Pulse width 300 usec, Duty cycle 2%

Thermal and Mechanical Characteristics

Storage temp range	T_{STG}	-55°C to 150°C
Operating junction temp range	T_J	-55°C to 150°C
Max thermal resistance	$R_{\theta JC}$	0.24°C/W Junction to case
Typical thermal resistance (greased)	$R_{\theta CS}$	0.12 °C/W Case to sink
Terminal Torque		35-40 inch pounds
Mounting Base Torque		20-25 inch pounds
Weight		1.1 ounces (32 grams) typical

COLORADO Microsemi
800 Hoyt Street
Broomfield, CO. 80020
PH: (303) 469-2161
FAX: (303) 466-3775
www.microsemi.com

3-14-00 Rev. 1

HS24230

Figure 1
Typical Forward Characteristics




Figure 2
Typical Reverse Characteristics




Figure 3
Typical Junction Capacitance




Figure 4
Forward Current Derating




Figure 5
Maximum Forward Power Dissipation

