



1) Cable length see text



### Basic features

<b>Approval/Conformity</b>	CE UKCA EAC WEEE
----------------------------	---------------------------

### Electrical connection

<b>Cable</b>	PVC Shielded gray, 2 m
<b>Cable diameter D</b>	5.80 mm
<b>Conductor cross-section</b>	0.25 mm <sup>2</sup>
<b>Connection</b>	D-Sub-Female, straight, 9-pin
<b>Connector configuration</b>	Straight
<b>Number of conductors</b>	4
<b>Number of pins</b>	9

### Electrical data

<b>Operating voltage U<sub>b</sub></b>	125 VDC / 125 VAC
<b>Rated current (40 °C)</b>	7.5 A

### Environmental conditions

<b>Cable temperature, fixed routing</b>	-30...80 °C
<b>Cable temperature, flexible routing</b>	-5...80 °C
<b>IP rating</b>	IP40

### Material

<b>Cable jacket material, note</b>	Shielded
<b>Cable jacket, material</b>	PVC

### Mechanical data

<b>Cable jacket, color</b>	gray
<b>Cable length L</b>	2.00 m

### Remarks

Connection cable: for internal service port RS 232 (on terminal strip) for connecting to PC.  
 1x MIN D female 9-pin threaded on with 3-conductor cable end incl. end ferrules  
 Enclosure rating per IEC 60529 or ISO 20653, only in screwed state with the associated mating piece.