


E-Series 2-Way 90° Power Divider 820 - 980 MHz




Features

- 2 Way
- 90 Degree
- Surface Mount



SM-88 Package

Note: Non Hermetic Package



Description

M/A-COM's ELPD-290 is a 2 Way 90° Power Divider in a low cost, surface mount package. Ideally suited for high volume cellular, wireless and CATV applications.

Electrical Specifications @25°C

Parameter	Units	Typical	Minimum	Maximum
Frequency Range	820 - 980	MHz	—	—
Insertion Loss	820 - 980 MHz	dB	0.7	1.2
Isolation	820 - 980 MHz	dB	20	18
Amplitude Unbalance	820 - 980 MHz	dB	—	1.2
Phase Unbalance	820 - 980 MHz	°	—	7.0°
Return Loss	820 - 980 MHz	dB	20	18

Please Note that the photograph above indicates package shape only, unit may be wired differently.

V2.00 S 1358 A

Absolute Maximum Ratings


Parameter	Absolute Maximum
Maximum Power Rating	1 Watt
Internal Load Dissipation	0.125 Watt
Pin Temp (10 Sec)	260°C
Storage Temperature	-55°C to 100°C

Functional Configuration


Function	Pin No.
Not Connected	—
External 50 Ohms	3
Ground	—
Case Ground	—
Input	1
Port 1	2
Port 2	4

Typical Performance @ +25°C


Insertion Loss




Isolation




Amplitude Unbalance




Phase Unbalance



Output Return Loss



Input Return Loss



V2.00 S 1358 A



M/A-COM Division of AMP Incorporated ■ North America: Tel. (800) 366-2266, Fax (800) 618-8883 ■ Asia/Pacific: Tel.+85 2 2111 8088, Fax +85 2 2111 8087 ■ Europe: Tel. +44 (1344) 869 595, Fax+44 (1344) 300 020

www.macom.com

AMP and Connecting at a Higher Level are trademarks. Specifications subject to change without notice.

