

■ Specifications :

- Voltage rating: 100V AC / DC
- Current rating: 2A AC / DC
- Withstanding voltage: 800V AC/minute
- Temperature range: -25°C~+85°C
- Insulation resistance:≥1000MΩ
- Contact resistance: ≤10mΩ
- After environmental testing: ≤20mΩ

Poles	Dimensions (mm)	
	A	B
02	2.00	6.00
03	4.00	8.00
04	6.00	10.00
05	8.00	12.00
06	10.00	14.00
07	12.00	16.00
08	14.00	18.00
09	16.00	20.00
10	18.00	22.00
11	20.00	24.00
12	22.00	26.00
13	24.00	28.00
14	26.00	30.00
15	28.00	32.00
16	30.00	34.00
17	32.00	36.00
18	34.00	38.00
19	36.00	40.00
20	38.00	42.00

X2016 W R X-XX B -XX SN XX
① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨

- ① Series No.
② Category: W-WAFER
③ Welding Board Angle: V-180° ; R-90°
④ Welding Way: Blank-DIP ; S-SMT
⑤ Row No.-Pin No.: XX-Single Row ; 2*XX-Double Row
⑥ Plug the Pin & Special No. :
B-With Groove ; Without Link Stopper
⑦ Material: N0 -PA66 94V-0 46-PA46 94-V0
⑧ Plating Category: G**-Gold Plated Contact
V**- All Gold-Plated
01-Gold Flash 02-2u" 03-3u"
05-5u" 10-10u" 15-15u"
SN-Bright Tin Plating (70-120u")
SN1-Bright Tin Plating (120u" Min).
0-No Plating Material
SW- Fog Tin Plating
HS-Hight temperature Tin
⑨ Color : Blank-Natural Color

X2016WR-XXB-46SN	Nylon 46 UL 94V-0	Brass	Tin-Plated	X2016H	1,000Pcs
X2016WR-XXB-N0SN	Nylon 66 UL 94V-0				
PART NO	Material	Material(Pin)	Finish(Pin)	Suitable XKB Terminal	Q'ty/Bag

For and on behalf of
XKB INDUSTRIAL PRECISION CO., LIMITED
香港星坤工業精密有限公司

		XKB INDUSTRIAL PRECISION CO., LIMITED				ANGULAR	±5°
△ X		香港星坤工業精密有限公司				L ≤ 4	±0.2
△ X						4 < L ≤ 16	±0.3
△ X						16 < L ≤ 63	±0.4
MARK		DESCRIPTION	DATE	REVISED	APPROVED	L > 63	±0.5
REVISIONS							UNSPECIFIED TOLERANCES
Authorized Signature(s)							

DSND		DATE		SCALE: N/A	MODEL TYPE: X2016WR-XXB-N0SN
DWN		DATE		VIEW: 	PART NO.:
CHKD		DATE		UNIT: mm	2.00 mm Crimp Style Connector
APPD		DATE		SIZE: A4	DWG NO.:
XKB INDUSTRIAL PRECISION CO., LIMITED					WEIGHT 1.0g
					SHEET 1/1
					REVISION A0