

MBR2045L(F,B,H)CT thru MBR20200L(F,B,H)CT

20A Schottky Barrier Rectifier

FEATURE


- High current capability
- Low forward voltage drop
- Low power loss, high efficiency
- High surge capability
- High ESD capability
- High temperature soldering guaranteed:
260°C/10s/0.25"(6.35mm) from case

MECHANICAL DATA

- Case: Molded with UL-94 Class V-0 recognized Flame Retardant Epoxy
- Mounting position: any

TYPICAL APPLICATIONS


For use in low voltage, high frequency rectifier of switching mode power supplies, freewheeling diodes, DC/DC converters and polarity protection application.



TO-220AB
MBR20XXLCT




ITO-220AB
MBR20XXLCT



TO-263
MBR20XXLCT



TO-262
MBR20XXLCT



Ratings at 25°C ambient temperature unless otherwise specified, Single phase, half wave, 60Hz, resistive or inductive load.

For capacitive load, derate current by 20%.

MAXIMUM RATINGS

Parameter		Symbol	MBR2045 LCT	MBR2060 LCT	MBR20100 LCT	MBR20150 LCT	units
Maximum Recurrent Peak Reverse Voltage		V_{RRM}	45	60	100	150	V
Maximum RMS Voltage		V_{RMS}	32	42	70	105	V
Maximum DC Blocking Voltage		V_{DC}	45	60	100	150	V
Maximum Average Forward Rectified Current at $T_C=90^{\circ}\text{C}$	total device	$I_{F(AV)}$	20.0				A
	per diode		10.0				
Peak Forward Surge Current 8.3ms Single Half sine-wave superimposed on rate load per diode (JEDEC method)		I_{FSM}	175				A
Junction Capacitance (Note1)		C_J	800		350		pF
Storage Temperature Range		T_{STG}	-55 to +150				°C
Operation Temperature Range		T_J	-55 to +150				°C

ELECTRONICAL CHARACTERISTICS

Parameter		Symbol	MBR2045 LCT	MBR2060 LCT	MBR20100 LCT	MBR20150 LCT	units
Maximum Forward Voltage Drop per diode at 10A (Note 2)		V_F	0.55	0.65	0.80	0.85	V
Maximum DC Reverse Current at rated	@ $T_C=25^{\circ}\text{C}$	I_R	0.15		0.1		mA
DC blocking voltage (Note 2)	@ $T_C=100^{\circ}\text{C}$		40.0		20.0		

THERMAL CHARACTERISTICS

Parameter	Symbol	ITO-220	TO-220	TO-262 TO-263	units
Typical Thermal Resistance (Note 3)	$R_{th(JC)}$	3.5	2.5	2.5	°C/W

Note:

1. Measured at 1.0 MHz and applied reverse voltage of 4.0Vdc.
2. Pulse test: 300 μs pulse width, 1% duty cycle.
3. Thermal Resistance from Junction to Case Mounted on heatsink.