

FEP-1601 Version: 1



16-Port Fast Ethernet PoE Switch, 250W

FEP-1601 is a 16-port 10/100Mbps Fast Ethernet Switch with Power over Ethernet (PoE) capability. With 16 dip switches, each PoE port can be manually set for On-Off control. FEP-1601 supports up to 30W on each LAN port when the DIP switch is in the ON position. Using a LevelOne PoE repeater, it is possible to extend the connection a further 100 meters, or even daisy-chain several PoE repeaters together for greater distances. Dual 10/100Mbps ports can connect with other edge switches or NVR as uplink ports.



1. LED Indicators
2. PoE Dip Switch
3. Power On/Off Switch

4. Power Socket
5. 10/100Mbps RJ-45 PoE Ports

Key Features

- IEEE 802.3x Flow Control protects against lost packets for reliable data transmission
- 10/100Mbps-Full/Half-duplex, Auto-Negotiation, Auto-MDI/MDIX
- PoE on/off control per port by dip switches
- Total PoE power budget: 250W, up to 30W per port
- 19-inch metal housing
-

Specifications

System Specifications

Standards & Protocols:

- IEEE 802.3 10-BASE-T, Ethernet
- IEEE 802.3u 100-BASE-TX, Fast Ethernet
- IEEE 802.3x Full-duplex Flow Control

**Buffer Memory:**

160KB

Connectors and Cabling:

16 x 10/100Base-TX RJ-45 PoE Ports

Button:

Power On/Off Switch , PoE Power On/Off Switch

Indicator:

Power, Active, 10/100M, PoE

Transmission Method:

Store-and-Forward

Power:

Power Consumption: < 250W

Power Input: 100-240V AC, 50-60 Hz, 5A, Internal Power Supply

Features

PoE:

Power Budget: Max. 240W

Power Output: 56V DC, up to 30W per port

Protection: PoE over current & PoE circuit sorting protection,

Pin Assignment: 4/5(+), 7/8(-)

Performance

Backplane (Gbps):

3.2Gbps

MAC Address Table:

4K

Data Transfer Rate:

10/100Mbps

Packet Forwarding Rate:

100Mbps port - 148,000pps

10Mbps port - 14,880pps

Environment

Temperature (°C):

Operating: 0°C ~ 45°C

Storage: - 40°C ~ 70°C

Humidity (Non-condensing):

Storage: 10% ~ 90%

Operating: 10% ~ 90%

Deployment:

Desktop and 19-inch rack-mountable

Physical Specifications

Dimensions (W x D x H mm):

480 x 118 x 44 mm


Weight (g):

2200g

Others

Approval and Compliance:
FCC, CE, RoHS

Diagram



Order Information

FEP-1601

Package Contents

FEP-1601
Power Cord
User Manual

No liability or responsibility for any errors or omissions in the content.
Specifications are subject to change without notice.
All mentioned brand names are registered trademarks and property of their owners.
Copyright © Digital Data Communications GmbH, Germany. All Rights Reserved.