

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:

0760351803

Status:

Active

Overview:

GbX I-Trac™ Backplane Connector System

Description:

GbX I-Trac™ Vertical Header Module, 1.85mm by 3.70mm Pitch, Unguided, Open Ends, 15 Rows, 8 Columns, 240 Circuits, Mating Pin Length 4.70mm

Documents:

3D Model

Packaging Specification PK-70873-586 (PDF)

Drawing (PDF)

RoHS Certificate of Compliance (PDF)

Product Specification PS-75710-999 (PDF)

Agency Certification

UL

E29179

General

Product Family

Backplane Connectors

Series

76035

Application

Backplane, Midplane, Orthogonal

Component Type

PCB Header

Overview

GbX I-Trac™ Backplane Connector System

Product Name

GbX I-Trac™

UPC

822350890564

Physical

Circuits (Loaded)

240

Circuits (maximum)

240

Color - Resin

Black

Durability (mating cycles max)

200

First Mate / Last Break

No

Flammability

94V-0

Guide to Mating Part

No

Keying to Mating Part

None

Material - Metal

High Performance Alloy (HPA)

Material - Plating Mating

Gold

Material - Plating Termination

Tin

Material - Resin

High Temperature Thermoplastic

Net Weight

7.006/g

Number of Columns

8

Number of Pairs

8, Open Pin Field

Number of Rows

15

Orientation

Vertical

PC Tail Length

2.10mm

PCB Locator

No

PCB Retention

None

PCB Thickness - Recommended

1.60mm

Packaging Type

Tray

Pitch - Mating Interface

1.85mm, 3.70mm

Pitch - Termination Interface

1.00mm, 2.70mm

Plating min - Mating

0.762µm

Plating min - Termination

0.762µm

Polarized to PCB

No

Stackable

Yes

Surface Mount Compatible (SMC)

Yes

Temperature Range - Operating

-55°C to +80°C

Termination Interface: Style

Through Hole - Compliant Pin

Electrical



Series image - Reference only

EU ELV

Not Relevant

EU RoHS

China RoHS

Compliant

REACH SVHC

Not Contained Per

-ED/79/2015 (17

December 2015)

Halogen-Free

Status

Low-Halogen

Need more information on product

environmental compliance?

Email productcompliance@molex.com

Please visit the [Contact Us](#) section for any

non-product compliance questions.

China ROHS

Green Image

ELV

Not Relevant

Search Parts in this Series

76035 Series

Mates With

76040 GbX I-Trac™ Right Angle Receptacle

Module

Use With

78237 GbX I-Trac™ Vertical Power

Receptacle. 75234 Backplane Free Standing

Guide Pin

Application Tooling | FAQ

Tooling specifications and manuals are

found by selecting the products below.

Crimp Height Specifications are then

contained in the Application Tooling

Specification document.

Global

Description

Product #

Current - Maximum per Contact	1.0A	Backplane Insertion	<u>0621005110</u>
Data Rate	12.0 Gbps	Tool for Signal	Contact Insertion
Shield Type	N/A	Press-In Tool for	<u>0622018619</u>
Shielded	No	Vertical Header 15-	Row, 8-Column
Voltage - Maximum	120V AC (RMS)/DC		
Solder Process Data			
Lead-freeProcess Capability	N/A		
Material Info			
Reference - Drawing Numbers			
Packaging Specification	PK-70873-586		
Product Specification	PS-75710-999		
Sales Drawing	SD-76035-001		

This document was generated on 06/13/2016

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION