



MOUNTING HOLE

SPECIFICATIONS

ADAPTER TYPE	SIMPLEX
FIBER TYPE	SINGLE MODE
MICRONS	9/125u
COLOR	NICKEL PLATED
INSERTION LOSS	-.2 dB
OPERATING TEMPERATURE	-40 TO 80° C
MATERIALS	ZIRCONIUM (ZrO2)
MATING DURABILITY	500 CYCLES



PASTERNAK ENTERPRISES, INC.

P.O BOX 16759, IRVINE, CA 92623
PHONE (949) 261-1920 FAX (949) 261-7451

WEB ADDRESS: www.pasternack.com
E-MAIL ADDRESS: sales@pasternack.com

COAXIAL & FIBER OPTICS

DWG TITLE

PE900040

DES.

FC APC SIMPLEX TO FC APC SIMPLEX
BULKHEAD

REV. B

FSCM NO. 53919

CAD FILE 101111

SCALE N/A

SIZE A

2231

NOTES:

1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
3. DIMENSIONS ARE IN INCHES [mm].