




- ▼ Fast Switching Characteristic
- ▼ Lower Gate Charge
- ▼ Small Footprint & Low Profile Package
- ▼ RoHS Compliant




$BV_{DSS}$	30V
$R_{DS(ON)}$	45m $\Omega$
$I_D$	5.5A

## Description

Advanced Power MOSFETs utilized advanced processing techniques to achieve the lowest possible on-resistance, extremely efficient and cost-effectiveness device.

The SOT-26 package is universally used for all commercial-industrial applications.



## Absolute Maximum Ratings

Symbol	Parameter	Rating	Units
$V_{DS}$	Drain-Source Voltage	30	V
$V_{GS}$	Gate-Source Voltage	$\pm 20$	V
$I_D @ T_A = 25^\circ C$	Continuous Drain Current <sup>3</sup> , $V_{GS}$ @ 4.5V	5.5	A
$I_D @ T_A = 70^\circ C$	Continuous Drain Current <sup>3</sup> , $V_{GS}$ @ 4.5V	4.4	A
$I_{DM}$	Pulsed Drain Current <sup>1</sup>	20	A
$P_D @ T_A = 25^\circ C$	Total Power Dissipation	2	W
	Linear Derating Factor	0.016	W/ $^\circ C$
$T_{STG}$	Storage Temperature Range	-55 to 150	$^\circ C$
$T_J$	Operating Junction Temperature Range	-55 to 150	$^\circ C$

## Thermal Data

Symbol	Parameter	Value	Unit
$R_{thj-a}$	Thermal Resistance Junction-ambient <sup>3</sup> Max.	62.5	$^\circ C/W$



# AP2604GY

## Electrical Characteristics @T<sub>j</sub>=25°C(unless otherwise specified)

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
$BV_{DSS}$	Drain-Source Breakdown Voltage	$V_{GS}=0V, I_D=250\mu A$	30	-	-	V
$\Delta BV_{DSS}/\Delta T_j$	Breakdown Voltage Temperature Coefficient	Reference to 25°C, $I_D=1mA$	-	0.02	-	V/°C
$R_{DS(ON)}$	Static Drain-Source On-Resistance <sup>2</sup>	$V_{GS}=10V, I_D=4.8A$	-	-	45	mΩ
		$V_{GS}=4.5V, I_D=2.4A$	-	-	65	mΩ
$V_{GS(th)}$	Gate Threshold Voltage	$V_{DS}=V_{GS}, I_D=250\mu A$	1	-	3	V
$g_{fs}$	Forward Transconductance	$V_{DS}=10V, I_D=4.8A$	-	7	-	S
$I_{DSS}$	Drain-Source Leakage Current (T <sub>j</sub> =25°C)	$V_{DS}=30V, V_{GS}=0V$	-	-	1	uA
	Drain-Source Leakage Current (T <sub>j</sub> =70°C)	$V_{DS}=24V, V_{GS}=0V$	-	-	25	uA
$I_{GSS}$	Gate-Source Leakage	$V_{GS}= \pm 20V$	-	-	±100	nA
$Q_g$	Total Gate Charge <sup>2</sup>	$I_D=4.8A$	-	6	10	nC
$Q_{gs}$	Gate-Source Charge	$V_{DS}=24V$	-	2	-	nC
$Q_{gd}$	Gate-Drain ("Miller") Charge	$V_{GS}=4.5V$	-	3	-	nC
$t_{d(on)}$	Turn-on Delay Time <sup>2</sup>	$V_{DS}=15V$	-	6	-	ns
$t_r$	Rise Time	$I_D=1A$	-	8	-	ns
$t_{d(off)}$	Turn-off Delay Time	$R_G=3.3\Omega, V_{GS}=10V$	-	15	-	ns
$t_f$	Fall Time	$R_D=15\Omega$	-	4	-	ns
$C_{iss}$	Input Capacitance	$V_{GS}=0V$	-	440	705	pF
$C_{oss}$	Output Capacitance	$V_{DS}=25V$	-	105	-	pF
$C_{rss}$	Reverse Transfer Capacitance	$f=1.0MHz$	-	35	-	pF

## Source-Drain Diode

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
$V_{SD}$	Forward On Voltage <sup>2</sup>	$I_S=4.8A, V_{GS}=0V$	-	-	1.2	V
$t_{rr}$	Reverse Recovery Time <sup>2</sup>	$I_S=4.8A, V_{GS}=0V,$	-	15	-	ns
$Q_{rr}$	Reverse Recovery Charge	$di/dt=100A/\mu s$	-	7	-	nC

### Notes:

- 1.Pulse width limited by Max. junction temperature.
- 2.Pulse width  $\leq 300\mu s$  , duty cycle  $\leq 2\%$ .
- 3.Surface mounted on 1 in<sup>2</sup> copper pad of FR4 board ; 156°C/W when mounted on min. copper pad.




Fig 1. Typical Output Characteristics




Fig 2. Typical Output Characteristics




Fig 3. On-Resistance v.s. Gate Voltage




Fig 4. Normalized On-Resistance v.s. Junction Temperature




Fig 5. Forward Characteristic of Reverse Diode




Fig 6. Gate Threshold Voltage v.s. Junction Temperature




Fig 7. Gate Charge Characteristics




Fig 8. Typical Capacitance Characteristics




Fig 9. Maximum Safe Operating Area




Fig 10. Effective Transient Thermal Impedance




Fig 11. Switching Time Waveform




Fig 12. Gate Charge Waveform