P-tec Corp. Tel:(866) 695 4162
2405 Commerce Circle Tel:(719) 589 3122
Alamosa CO 81101 Fax:(719) 589 3592
www.p-tec.net

PL309 Series 3mm LED Right Angle Bi-Level Holder

Features

*Space Saving Bi-Level PCB Indicator
*Housing Material Black Nylon UL94V-2
*High Light Output
*2 Super Bright Red Leds with Color Diffused Lens used
*Leds are arranged from Top to Bottom
*RoHS Compliant

Absolute Maximum Ratings at T_A = 25°C

Power Dissipation	66mW
Reverse Voltage (<100 µA)	4.0V
Max Forward Current	30mA
Peak Forward Current (1/10 Duty Cycle, 0.1ms Pulse Width)	100mA
Operating Temperature Range	-25°C to +85°C
Storage Temperature Range	-40°C to +100°C
Soldering Temperature (1.6 mm below body)	260°C for 5 seconds

Electrical & Optical Characteristics at T_A = 25°C

Part Number	Emitting Color	Chip Material	Peak Wave Length	Dominant Wave Length	Viewing Angle 2θ ½	Forward Voltage @20mA (V)		Luminous Intensity @20mA (mcd)	
Color Diffused Lens			nm	nm	Deg	Typ	Max	Min	Typ
PL309-2R21	Deep Red	AlGaAs	660	643	55°	1.8	2.2	60.0	100.0

All dimensions are in **Millimeters**. Tolerance is ± 0.5mm unless otherwise specified.

