

LOC	DIST	REVISIONS					
		P	LTR	DESCRIPTION	DATE	DWN	APVD
AD	00		C3	REVISED PER ECO-11-010839	25MAY11	RK	HMR

SPECIFICATIONS:

MATERIALS:
BASE: PPS UL94V-0
COVER: PPS UL94V-0
ACTUATOR: LCP UL94V-0
MOVING CONTACT: COPPER ALLOY, GOLD OVER NICKEL PLATE
FIXED CONTACT/TERMINAL: COPER ALLOY, GOLD OVER NICKEL PLATE

ELECTRICAL:
CONTACT RATING: NON-SWITCHING 100mA @ 50 VDC
SWITCHING: 25mA @ 24 VDC.
INITIAL CONTACT RESISTANCE: 100mΩ MAX. @ 2 VDC, 10 mA.
INSULATION RESISTANCE: 100 MEGOHMS MIN. @ 100 VDC.
DIELECTRIC STRENGTH: 300 VAC. 1 MINUTE.
LIFE: 1,000 CYCLES.

MECHANICAL:
OPERATING FORCE: 600G MAX.

ENVIRONMENTAL:
OPERATING TEMPERATURE: -22°F TO +185°F (-30°C TO +85°C).
STORAGE TEMPERATURE: -49°F TO +212°F (-45°C TO +100°C).
SOLDER HEAT RESISTANCE PER 109-201, CONDITION B
SOLDERABILITY PER JIS C 0050 & JIS C 0053

NOTES:

- 1

PARTS WITH 'ON' SUFFIX SUPPLIED IN THE ON POSITION.
- 2

SUPPLIED WITH TAPE SEAL STANDARD.
- 3

FOR TAPE AND REEL PACKAGING- PART NO. GDHXXSTR
SEE MODEL NUMBER CHART BELOW.
- 4

FOR NO SEAL OPTION = NS.
- 5

ALL MATERIALS AND FINISHES SHALL COMPLY WITH EU DIRECTIVE
2002/95/EC OF 27 JAN 2003 (ROHS)
- 6

OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

	11.43[.450]	13.82[.544]	10	NONE	GDH010STRNS04	1-1571983-6
1	1.27[.050]	3.66[.144]	2	TAPE	GDH02STRON04	1-1571983-5
	11.43[.450]	13.82[.544]	10	TAPE	GDH010STR04	1-1571983-4
	11.43[.450]	13.82[.544]	10	TAPE	GDH010S04	1-1571983-3
4	8.89[.350]	11.28[.444]	8	NONE	GDH08STRNS04	1-1571983-2
	8.89[.350]	11.28[.444]	8	TAPE	GDH08STR04	1-1571983-1
	8.89[.350]	11.28[.444]	8	TAPE	GDH08S04	1-1571983-0
	6.35[.250]	8.74[.344]	6	TAPE	GDH06STR04	1571983-9
	6.35[.250]	8.74[.344]	6	TAPE	GDH06S04	1571983-8
1	3.81[.150]	6.20[.244]	4	TAPE	GDH04STRON04	1571983-7
4	3.81[.150]	6.20[.244]	4	NONE	GDH04STRNS04	1571983-6
	3.81[.150]	6.20[.244]	4	TAPE	GDH04STR04	1571983-5
	3.81[.150]	6.20[.244]	4	TAPE	GDH04S04	1571983-4
	1.27[.050]	3.66[.144]	2	TAPE	GDH02STR04	1571983-3
16	1.27[.050]	3.66[.144]	2	TAPE	GDH02SON04	1571983-2
	1.27[.050]	3.66[.144]	2	TAPE	GDH02S04	1571983-1
	M	L	POLE	SEAL	OLD T&B P/N	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN

R BROWN

15MAR05

CHK

M SARVER

15MAR05

APVD

M SARVER

15MAR05

PRODUCT SPEC

APPLICATION SPEC

WEIGHT

CUSTOMER DRAWING

DIMENSIONS:

mm [INCHES]

0 PLC

1 PLC

2 PLC

3 PLC

4 PLC

ANGLES

FINISH

± -

± -

± 0.25 [.010]

± -

± -

± 1°

-

TE Connectivity

DIP SWITCH

GDH SERIES

SIZE

CAGE CODE

DRAWING NO

RESTRICTED TO

A2

00779

C=1571983

-

SCALE





SHEET

REV

8:1

1 of 1

C3



P.C.B. PAD LAYOUT
PCB LAYOUT TOLERANCES ±002
ON ALL DIMENSIONS